



May 10, 2023

City of Lone Tree  
Attn: Jacob James, City Engineer  
Public Works Department  
9220 Kimmer Drive, Suite 100  
Lone Tree, CO 80124

**RE: *Floor & Decor – Lone Tree  
Lot 1A, Block 2, of the Parkway Subdivision Filing No. 3  
Final Drainage Conformance Letter***

The following letter is intended to serve as a final drainage conformance letter for Floor & Decor – Lone Tree, “The Project,” which is located on Lot 1A, Block 2 of the Parkway Subdivision Filing No. 3, 3<sup>rd</sup> Amendment site. The Project falls within the overall Parkway Subdivision Filing No. 3 development. The storm design for this site was previously approved under the *Phase III Drainage Study, Project Majestic (December 1994)*, (the Phase III Report). Excerpts from the Phase III Report are attached. As such, the project described herein is subject to meeting the criteria and expected design flows as outlined in the Phase III drainage Report.

## **PROJECT DESCRIPTION**

The Project consists of expanding the existing building located within Lot 1A, Block 2 of the Filing No. 3 site, and will add customer pick up on the northeast corner of the building, as well as adding to the sidewalk along the east of the building. The existing detention pond will be retrofitted to provide water quality for the site as well.

The site is served by existing permanent stormwater infrastructure as designed and constructed with the Phase III Report. The site currently conveys stormwater via a network of existing surface inlets routed to an underground storm sewer system. This storm sewer system conveys runoff to existing detention pond located in the western corner of the site. The total area of disturbance for the Project is approximately 0.87 acres.

Runoff produced by the proposed improvements during the minor (10-year) and major (100-year) storm events is less than what the site was designed for, and the percent imperviousness for the site is less than what was assumed for the ultimate condition in the Phase III Report. Therefore, it is not anticipated that the proposed improvements will negatively impact the existing storm infrastructure. A detailed comparison is listed in the Proposed Drainage Conditions section of this letter.

## **DESIGN CRITERIA AND APPROACH**

The project is subject to the design criteria as stated in the Phase III Report, as well as City water quality criteria that has been developed since the original pond was construction. The previous Phase III Report accounted for 16.34 acres of area in Basins A, B, C, D, E, F, G, H, I, and J, producing runoff that flowed downstream through a proposed storm sewer system to the existing detention pond in the western corner of the site. The pond was sized to provide detention for the site, but not water quality, and ultimately discharges to another existing detention pond via swale. This existing detention

pond was designed with the Parkway Master Drainage Study, by Costin Engineering Company in July 1984.

The Phase III Report states that the pond was sized assuming the ultimate buildout for the site to be 80% impervious. Based on the survey of the existing conditions and with our proposed improvements, the site is 3% below the maximum allowable percent impervious. Detention is provided on site via an existing detention pond designed with the previously approved Phase III Report. A description of basin modifications is provided in the Proposed Drainage Conditions of this conformance letter. There are no anticipated impacts to existing irrigation facilities.

### **PROPOSED DRAINAGE CONDITIONS**

The Project will include the expansion of the existing building along the northeast corner and will add 14,469 sf, sidewalk and entrance along the east of the building, new curb and gutter along the northern landscape island, customer pickup, and associated utilities. The existing pond discharge structure will be removed and replaced with a parallel wall outlet structure consisting of an orifice plate, trash grate, and discharge pipe. The pond already has an existing trickle channel, and the new discharge structure has been designed to match the existing elevations. This retrofit enables the existing EDB to provide the required water quality capture volume (WQCV) based on the assumed 80% ultimate build out condition in the original Phase III report. The design calculations for the WQCV can be found in **Attachment 3**.

The site evaluation and proposed retrofit assumed the detention pond has been restored to the original approved condition (remediated). This will be completed by the current property owner before completion of the proposed retrofit, and project close out will not be issued by the City of Lone Tree until remediation and retrofit are complete and accepted by the City.

Existing drainage patterns will be maintained with the site improvements. The basins from the previous Phase III design that are impacted by the proposed improvements are D, F, G, H, and I. Basins with the " ' " designation represent a change in basin area. The revisions consist of land use changes, grading adjustments, and adjustment to basin boundaries. The differences in C values can be attributed to the previous Phase III Report using outdated criteria from Mile High Flood District, and the criteria used for the calculations in this letter being current. Full rational calculation for the site can be found in **Attachment 3**. The proposed modification within each basin are as follows:

#### **Basin C**

Basin C drainage area, inflow, and discharge will all remain the same as defined in the original Phase III report. The only proposed modification within this basin is to remove the existing discharge structure and replace it with a parallel wall outlet structure with an orifice plate and trash grate. The existing discharge pipe will remain as well as the existing trickle channel. The proposed discharge structure will match the existing inverts for both elements. The overflow spillway will be widened slightly to provide adequate flood control. These improvements enable the existing detention pond to provide water quality for the ultimate condition assumed in the original Phase III report.

## Basin D

As it exists, the concrete in Basin D near the existing inlet at Design Point 3 has a depression that is preventing stormwater from the east to reach the inlet. This depression was noticed while in the field and will be filled in as part of the site improvements. This will not impact the imperviousness or existing drainage patterns in the basin, and stormwater runoff will still flow to the inlet at Design Point 3.

## Basin F'

Previously Basin F consisted of 1.76 acres of building on the site. Basin F' proposes a building expansion of 14,469 sf to the north and east, giving the basin a total roof area of 2.14 acres. **Attachment 2** depicts this area visually. The percent impervious for this basin will remain the same, and runoff will still flow to Design Point 11.

## Basin G

While the delineated area of 0.45 acres for Basin G will not be impacted with the proposed improvements, the site will be adding 831 sf of sidewalk to the western side of the basin along the existing building. This improvement will not negatively impact existing drainage patterns and will still drain to the inlet at Design Point 6. Previously, Basin G had 0.19 acres of landscape area, 0.23 acres of pavement, and 0.03 acres of sidewalk. Based off of the survey of existing conditions and the sidewalk expansion, Basin G now has 0.19 acres of landscape area, 0.20 acres of pavement, and 0.06 acres of sidewalk, having a percent impervious of 57%.

## Basin H'

Previously Basin H consisted of 0.64 total acres, with 0.33 acres of paving area, and 0.31 acres of landscape area. Basin H' will reduce to a total of 0.52 acres due to the building expansion and will add 1,854 sf of sidewalk. Based off the survey of existing conditions and the proposed improvements, Basin H' has 0.24 acres of paved area, 0.04 acres of sidewalk, and 0.24 acres of landscape area, having a percent imperviousness of 57%. The proposed improvements will not negatively impact the existing drainage patterns and the basin still drains to Design Point 7.

## Basin I'

Previously Basin I consisted of 0.88 total acres, with 0.61 acres of paving area, and 0.27 acres of landscape area. Basin I' will reduce to a total of 0.68 acres due to the building expansion andp will reduce landscape area based off of the needed with of the drive aisle along the north of the building. Based off of the survey of existing conditions and the proposed improvements, Basin I' has 0.48 acres of paved area, 0.01 acres of sidewalk, and 0.19 acres of landscape area, having a percent imperviousness of 72%. The proposed improvements will not negatively impact the existing drainage patterns and the basin still drains to Design Point 8.

The previous Phase III drainage Report assumed the ultimate condition for the site to be 80% impervious. Based on the survey of the existing conditions, as well as the proposed improvements for the site, the proposed site is to be 77% impervious, 3% below the maximum impervious percentage

of the original design. The Phase III Report calculated the total runoff for the 5-year event to be 58.02 cfs, and the 100-year event to be 109.18 cfs. The proposed site produces 47.87 cfs for the 5-year event, and 107.64 cfs for the 100-year event, reducing the overall flow going to the existing detention pond for the site. Time of concentration values used for the rational calculation in basins not impacted by the proposed improvements were the same values used in the Phase III Report. This was done for consistency and lack of existing topography for the southern and eastern portions of the site. See **Attachment 1 – Runoff Comparison Table** for a direct runoff comparison.

**Attachment 2 – Proposed Drainage Condition Map**, illustrates the modified basin map for our proposed site, and **Attachment 4** contains pages from the previous Phase III Drainage Report.

## DETENTION & WATER QUALITY

In the previous Phase III Report for the site, a detention pond was designed and located in the western corner of the site. The pond used the assumption of 80% impervious when calculating the required volume for the pond. The pond was designed to have a total volume of 2.08 ac-ft for the 100-year storm event, and 1.22 ac-ft for the 10-year event. The pond volume does not account for Basin J, as this basin flows offsite to the east into S. Yosemite St. The pond volume and existing design also does not account for water quality.

The existing pond will be retrofitted to include water quality for the site. Water quality evaluation was completed based on City and MHFD criteria. The existing discharge structure will be removed and replaced with a new parallel wall outlet structure with an orifice plate and trash grate. The existing emergency overflow spillway will be widened to provide adequate flood control. Design calculations for the new discharge structure and spillway are included in **Attachment 3**.

With the proposed improvements for this project, site has a percent impervious of 77%, and using the same volume calculation as the Phase III Report, requires 1.97 ac-ft of detention volume, which complies with the original pond design.

The detention pond discharges to a swale designed with the Phase III Report, and ultimately outfalls into an existing detention pond downstream. See **Attachment 3** for proposed condition calculation and **Attachment 4** for pond calculations from the Phase III Report, as well as other relevant experts.

The Property Owner is aware that the pond on site is currently not maintained and operating as designed. The Property Owner is aware that the pond needs to be brought into compliance as part of this project.

## CONCLUSIONS

Based on being below the maximum percent imperviousness for the site, the retrofitting of the pond for water quality, as well as reducing the overall runoff produced by the site for both the minor and major storm events, the proposed improvements associated with this Project are in conformance with *Phase III Drainage Study, Project Majestic (December 1994)* and are in compliance with City of Lone Tree requirements.

Should you have any questions or concerns, please do not hesitate to contact me at (303) 228-2300.

Sincerely,  
KIMLEY-HORN



Shannon Petersen, P.E.  
Project Manager

**References:**

*Phase III Drainage Study, Project Majestic (December 1994) by Martin/Martin*

**Attachments:**

- Attachment 1: Runoff Comparison Table
- Attachment 2: Proposed Drainage Condition Map
- Attachment 3: Rational and Water Quality Calculations
- Attachment 4: Pages from Approved *Phase III Drainage Study, Project Majestic (December 1994)*

## ATTACHMENT 1: RUNOFF COMPARISON TABLE

Phase III Report					
Basin	Area (ac)	C5	C100	Q5 (cfs)	Q100 (cfs)
A	6.01	0.81	0.87	21.92	40.1
B	1.99	0.82	0.88	8	15.76
C	1.08	0.01	0.2	0.48	1.75
D	1.49	0.67	0.75	4.9	10.08
E	1.76	0.85	0.9	7.35	14.22
F	1.76	0.85	0.9	7.35	14.22
G	0.45	0.51	0.62	1.68	2.24
H	0.64	0.46	0.58	2.16	2.89
I	0.88	0.61	0.71	2.65	5.58
J	0.28	0.88	0.93	1.23	2.34
<b>Total</b>	<b>16.34</b>	--	--	<b>57.72</b>	<b>109.18</b>

Proposed Improvements					
Basin	Area (ac)	C5	C100	Q5 (cfs)	Q100 (cfs)
A	6.01	0.71	0.82	17.43	37.76
B	1.99	0.76	0.85	7.13	14.83
C	1.08	0.05	0.49	0.04	3.31
D	1.49	0.62	0.77	4.26	10.20
E	1.76	0.77	0.85	6.32	13.20
F'	2.14	0.77	0.85	7.68	16.04
G	0.45	0.50	0.71	0.95	2.63
H'	0.52	0.50	0.71	1.02	2.83
I'	0.68	0.63	0.78	1.99	4.69
J	0.28	0.80	0.86	1.05	2.14
<b>Total</b>	<b>16.40</b>	--	--	<b>47.87</b>	<b>107.64</b>

ATTACHMENT 2: PROPOSED DRAINAGE CONDITON MAP





**PARKWAY SUBDIVISION FILING NO. 3, THIRD AMENDMENT, LOT 1A, BLOCK 2**  
 LOCATED IN THE NORTHWEST QUARTER OF SECTION 3, TOWNSHIP 6 SOUTH, RANGE 67 WEST OF THE 6TH P.M. CITY OF LONE TREE, COUNTY OF DOUGLAS, STATE OF COLORADO

K:\DEN\_Civil\096198011\_Floor & Decor Lone Tree\CADD\PlanSheets\CD\096198011\_DRAINAGE.dwg Healey, Sean 5/10/2023 2:48 PM



**LEGEND**

- PROPERTY LINE
- - - EASEMENT LINE
- BASIN BOUNDARY
- PROP. MAJOR CONTOUR
- PROP. MINOR CONTOUR
- PROP. CURB & GUTTER
- PROP. OUTLET STRUCTURE
- PROP. EMERGENCY SPILLWAY
- EX. RIPRAP
- EX. CONTOUR
- EX. ASPHALT
- EX. STORM SEWER
- EX. STORM STRUCTURE
- EX. WATER LINE
- EX. SANITARY LINE
- EX. GAS LINE
- EX. FIRE HYDRANT
- EX. WATER FIXTURE
- EX. SS MANHOLE
- EX. RIGHT OF WAY

4:1 1.00%  
 → PROPOSED SLOPE ARROW  
 → PROPOSED FLOW ARROW  
 → EXISTING FLOW ARROW

--- PROPOSED 6" CONCRETE SIDEWALK  
 --- EXISTING CONCRETE  
 --- PROPOSED 6" PCCP  
 --- HEAVY-DUTY CONCRETE RECONSTRUCTION

A B C D  
 A - DRAINAGE BASIN  
 B - BASIN ACREAGE  
 C - 5-YEAR RUNOFF COEFFICIENT  
 D - 100-YEAR RUNOFF COEFFICIENT

A1 DESIGN POINT

**Kimley»Horn**  
 PROJECT NAME: Floor & Decor DATE: 2/7/2023  
 PROJECT NUMBER: 96198011  
 CALCULATED BY: SWH  
 CHECKED BY: SLP

**RATIONAL CALCULATIONS SUMMARY**

DESIGN POINT	TRIBUTARY BASINS	TRIBUTARY AREA (AC)	PEAK FLOWS (CFS)	
			G5	Q100
<b>On-Site Basins</b>				
1, 1A	A	6.01	17.43	37.76
2, 2A	B	1.99	7.13	14.63
3	C	1.08	0.04	3.31
4	D	1.49	4.26	10.20
5	E	1.76	6.32	13.20
6	F	2.14	7.68	16.04
7	G	0.45	0.95	2.63
8	H	0.52	1.23	3.10
9	I	0.58	1.99	4.69
10	J	0.28	1.05	2.14
<b>TOTAL</b>		<b>16.40</b>	<b>48.08</b>	<b>107.91</b>

NORTH

GRAPHIC SCALE IN FEET  
 0 20 40 80

CITY OF LONE TREE  
 DATE \_\_\_\_\_

THESE CONSTRUCTION PLANS HAVE BEEN REVIEWED BY THE CITY OF LONE TREE FOR STREET AND DRAINAGE IMPROVEMENTS ONLY.

ENGINEERING DIVISION ACCEPTANCE BLOCK

MATCHLINE - SEE SHEET 13

**Kimley»Horn**  
 KIMLEY-HORN AND ASSOCIATES, INC.  
 6200 South Syracuse Way, Suite 300  
 Greenwood Village, Colorado 80111 (303) 228-2300

DESIGNED BY: SLP  
 DRAWN BY: JAQ  
 CHECKED BY: SLP  
 DATE: 04/28/2023

**PARKWAY SUBDIVISION FILING NO. 3,  
 THIRD AMENDMENT, LOT 1A, BLOCK 2**  
 CITY OF LONE TREE, COUNTY OF DOUGLAS  
 CONSTRUCTION DOCUMENTS  
**DRAINAGE PLAN**

PRELIMINARY  
 FOR REVIEW ONLY  
 NOT FOR CONSTRUCTION  
 Kimley»Horn  
 Kimley-Horn and Associates, Inc.

PROJECT NO.  
 096198011


DRAWING NAME  
 096198011\_DRAINAGE.DWG

12 OF 34



**PARKWAY SUBDIVISION FILING NO. 3, THIRD AMENDMENT, LOT 1A, BLOCK 2**  
 LOCATED IN THE NORTHWEST QUARTER OF SECTION 3, TOWNSHIP 6 SOUTH, RANGE 67 WEST OF THE 6TH P.M. CITY OF LONE TREE, COUNTY OF DOUGLAS, STATE OF COLORADO

MATCHLINE - SEE SHEET 12



**LEGEND**

- PROPERTY LINE
- - - EASEMENT LINE
- - - - - BASIN BOUNDARY
- - - - - PROP. MAJOR CONTOUR
- - - - - PROP. MINOR CONTOUR
- - - - - PROP. CURB & GUTTER
- - - - - PROP. OUTLET STRUCTURE
- - - - - PROP. EMERGENCY SPILLWAY
- EX. RIPRAP
- EX. CONTOUR
- EX. ASPHALT
- EX. STORM SEWER
- EX. STORM STRUCTURE
- EX. WATER LINE
- EX. SANITARY LINE
- EX. GAS LINE
- EX. FIRE HYDRANT
- EX. WATER FIXTURE
- EX. SS MANHOLE
- EX. RIGHT OF WAY

4:1 1.00%  
 → PROPOSED FLOW ARROW  
 → EXISTING FLOW ARROW

PROPOSED 6" CONCRETE SIDEWALK  
 EXISTING CONCRETE  
 PROPOSED 6" PCCP  
 HEAVY-DUTY CONCRETE RECONSTRUCTION

A  
 B C D  
 A1

A - DRAINAGE BASIN  
 B - BASIN ACREAGE  
 C - 5-YEAR RUNOFF COEFFICIENT  
 D - 100-YEAR RUNOFF COEFFICIENT

A1 DESIGN POINT

**Kimley»Horn**

PROJECT NAME: Floor & Décor DATE: 2/7/2023  
 PROJECT NUMBER: 96198011  
 CALCULATED BY: SWH  
 CHECKED BY: SLP

**RATIONAL CALCULATIONS SUMMARY**

DESIGN POINT	TRIBUTARY BASINS	TRIBUTARY AREA (AC)	PEAK FLOWS (CFS)	
			Q5	Q100
<b>On-Site Basins</b>				
1, 1A	A	6.01	17.43	37.76
2, 2A	B	1.99	7.13	14.83
9	C	1.08	0.04	3.31
3	D	1.49	4.26	10.20
4	E	1.76	6.32	13.20
5	F'	2.14	7.68	16.04
6	G	0.45	0.95	2.63
7	H'	0.52	1.23	3.10
8	I'	0.68	1.99	4.69
10	J	0.28	1.05	2.14
<b>TOTAL</b>		<b>16.40</b>	<b>48.08</b>	<b>107.91</b>

NORTH

GRAPHIC SCALE IN FEET  
 0 20 40 80

CITY OF LONE TREE

DATE

THESE CONSTRUCTION PLANS HAVE BEEN REVIEWED BY THE CITY OF LONE TREE FOR STREET AND DRAINAGE IMPROVEMENTS ONLY.

ENGINEERING DIVISION ACCEPTANCE BLOCK

**Kimley»Horn**

KIMLEY-HORN AND ASSOCIATES, INC.  
 6200 South Syracuse Way, Suite 300  
 Greenwood Village, Colorado 80111 (303) 228-2300

DESIGNED BY: SLP  
 DRAWN BY: JAQ  
 CHECKED BY: SLP  
 DATE: 04/28/2023

**PARKWAY SUBDIVISION FILING NO. 3,  
 THIRD AMENDMENT, LOT 1A, BLOCK 2**  
 CITY OF LONE TREE, COUNTY OF DOUGLAS  
 CONSTRUCTION DOCUMENTS  
**DRAINAGE PLAN**

PRELIMINARY  
 FOR REVIEW ONLY  
 NOT FOR CONSTRUCTION

PROJECT NO.  
 096198011


DRAWING NAME  
 996198011\_DRAINAGE.DWG

**13 OF 34**

K:\DEN\_Civil\096198011\_Floor & Décor Lone Tree\CADD\PlanSheets\CD\096198011\_DRAINAGE.dwg Healey, Sean 5/10/2023 2:48 PM




**PARKWAY SUBDIVISION FILING NO. 3, THIRD AMENDMENT, LOT 1A, BLOCK 2**  
 LOCATED IN THE NORTHWEST QUARTER OF SECTION 3, TOWNSHIP 6 SOUTH, RANGE 67 WEST OF THE 6TH P.M. CITY OF LONE TREE, COUNTY OF DOUGLAS, STATE OF COLORADO




**1 OUTLET STRUCTURE DIMENSIONS**  
N.T.S.


NOTE: CONTRACTOR TO ENSURE ACCESSIBILITY TO BOTH SECTIONS OF OUTLET STRUCTURE.



**5 EMERGENCY SPILLWAY**  
N.T.S.




**2 OUTLET STRUCTURE CROSS SECTION**  
N.T.S.




**3 ORIFICE PLATE DETAIL**  
N.T.S.

**ORIFICE PLATE NOTES**

1. PROVIDE CONTINUOUS NEOPRENE GASKET MATERIAL BETWEEN THE ORIFICE PLATE AND CONCRETE.
2. BOLT PLATE TO CONCRETE 12" MAX. ON CENTER.



**4 OUTFALL PIPE RESTRICTOR PLATE DETAIL**  
N.T.S.



**6 TRASH RACK**  
N.T.S.

CITY OF LONE TREE

DATE \_\_\_\_\_

THESE CONSTRUCTION PLANS HAVE BEEN REVIEWED BY THE CITY OF LONE TREE FOR STREET AND DRAINAGE IMPROVEMENTS ONLY.

ENGINEERING DIVISION ACCEPTANCE BLOCK



KIMLEY-HORN AND ASSOCIATES, INC.  
 6200 South Syracuse Way, Suite 500  
 Greenwood Village, Colorado 80111 (303) 228-2300

**PARKWAY SUBDIVISION FILING NO. 3,  
 THIRD AMENDMENT, LOT 1A, BLOCK 2**  
 CITY OF LONE TREE, COUNTY OF DOUGLAS  
 CONSTRUCTION DOCUMENTS  
 STANDARD DETAILS

**PRELIMINARY**  
 FOR REVIEW ONLY  
 NOT FOR  
 CONSTRUCTION  
 Kimley-Horn

PROJECT NO.  
096198011

DRAWING NAME  
096198011 STD  
DETAILS.DWG

REVISION	BY	DATE	APPR

K:\DEN\_Civil\096198011\_Floor & Decor Lone Tree\CADD\PlanSheets\CD\096198011 STD DETAILS.dwg Hedley, Sean 5/10/2023 2:48 PM

## ATTACHMENT 3: RATIONAL AND WATER QUALITY CALCULATIONS



**STANDARD FORM SF-1  
RUNOFF COEFFICIENTS - IMPERVIOUS CALCULATION**

PROJECT NAME: Floor & Décor  
 PROJECT NUMBER: 96198011  
 CALCULATED BY: SWH  
 CHECKED BY: SLP

DATE: 2/7/2023

SOIL: C/D

LAND USE:	PAVED AREA	ROOF AREA	LANDSCAPE AREA	CONCRETE AREA
2-YEAR COEFF.	0.83	0.74	0.01	0.74
5-YEAR COEFF.	0.85	0.77	0.05	0.77
10-YEAR COEFF.	0.87	0.79	0.15	0.79
100-YEAR COEFF.	0.89	0.85	0.49	0.85
IMPERVIOUS %	100%	90%	2%	90%

DESIGN BASIN	DESIGN POINT	PAVED AREA (AC)	ROOF AREA (AC)	LANDSCAPE AREA (AC)	CONCRETE AREA (AC)	TOTAL AREA (AC)	C(2)	C(5)	C(10)	C(100)	Imp %
<b>On-Site Basins</b>											
A	1, 1A	4.73	0.03	1.00	0.24	6.01	0.69	0.71	0.75	0.82	83%
B	2, 2A	1.58	0.00	0.19	0.21	1.99	0.74	0.76	0.79	0.85	89%
C	9	0.00	0.00	1.08	0.00	1.08	0.01	0.05	0.15	0.49	2%
D	3	0.21	0.00	0.34	0.95	1.49	0.59	0.62	0.66	0.77	72%
E	4	0.00	1.76	0.00	0.00	1.76	0.74	0.77	0.79	0.85	90%
F	5	0.00	2.14	0.00	0.00	2.14	0.74	0.77	0.79	0.85	90%
G	6	0.20	0.00	0.19	0.06	0.45	0.47	0.50	0.55	0.71	57%
H	7	0.30	0.00	0.18	0.04	0.52	0.54	0.57	0.62	0.75	66%
I	8	0.48	0.00	0.19	0.01	0.68	0.60	0.63	0.67	0.78	73%
J	10	0.21	0.00	0.01	0.05	0.28	0.77	0.80	0.82	0.86	93%
<b>BASIN SUBTOTAL</b>		<b>7.71</b>	<b>3.93</b>	<b>3.19</b>	<b>1.57</b>	<b>16.40</b>	<b>0.64</b>	<b>0.67</b>	0.70	<b>0.80</b>	<b>78%</b>
		<b>47%</b>	<b>24%</b>	<b>19%</b>	<b>10%</b>	<b>100%</b>					

**STANDARD FORM SF-2  
Time of Concentration**

PROJECT NAME: Floor & Décor  
 PROJECT NUMBER: 96198011  
 CALCULATED BY: SWH  
 CHECKED BY: SLP

DATE: 2/7/2023

SUB-BASIN DATA			INITIAL TIME (T <sub>i</sub> )			TRAVEL TIME (T <sub>t</sub> )					T <sub>c</sub> CHECK (URBANIZED BASINS)				FINAL T <sub>c</sub>	
DESIGN BASIN (1)	AREA Ac (2)	C5 (3)	LENGTH Ft (4)	SLOPE % (5)	T <sub>i</sub> Min. (6)	LENGTH Ft. (7)	SLOPE % (8)	C <sub>v</sub> (9)	VEL fps (11)	T <sub>t</sub> Min. (12)	COMP. t <sub>c</sub> (13)	TOTAL LENGTH (14)	TOTAL SLOPE (15)	TOTAL IMP. (16)	T <sub>c</sub> Min. (17)	Min.
<b>On-Site Basins</b>																
A	6.01	0.71	30	2.0%	3.1	720	1.5%	20.0	2.4	4.9	8.0	750	1.5%	83%	16.8	8.0
B	1.99	0.76				380	2.5%	20.0	3.1	2.0	2.0	380	2.5%	89%	12.7	5.0
C	1.08	0.05	60	2.0%	11.8	300	3.3%	20.0	3.6	1.4	13.2	360	3.1%	2%	29.3	13.2
D	1.49	0.62	40	15.0%	2.3	330	1.3%	20.0	2.3	2.4	4.7	370	2.8%	72%	15.8	5.0
E	1.76	0.77				200	2.0%	20.0	2.8	1.2	1.2	200	2.0%	90%	11.8	5.0
F'	2.14	0.77				200	2.0%	20.0	2.8	1.2	1.2	200	2.0%	90%	11.8	5.0
G	0.45	0.50	55	2.0%	6.5	135	50.0%	20.0	14.1	0.2	6.6	190	36.1%	57%	16.6	6.6
H'	0.52	0.57	55	2.0%	5.7	160	1.0%	20.0	2.0	1.3	7.0	215	1.3%	66%	16.6	7.0
I'	0.68	0.63	45	8.2%	2.9	233	1.6%	20.0	2.5	1.5	4.4	278	2.7%	73%	15.1	5.0
J	0.28	0.80				230	4.0%	20.0	4.0	1.0	1.0	230	4.0%	93%	11.0	5.0

$$t_i = \frac{0.395(1.1 - C_s)\sqrt{L_i}}{S_o^{0.33}}$$

$$t_i = \frac{L_i}{60K\sqrt{S_o}} = \frac{L_i}{60V_i}$$

$$t_i = (26 - 17i) + \frac{L_i}{60(14i + 9)\sqrt{S_i}}$$









PROJECT NAME: Floor & Décor  
PROJECT NUMBER: 96198011  
CALCULATED BY: SWH  
CHECKED BY: SLP

DATE: 2/7/2023


**RATIONAL CALCULATIONS SUMMARY**

DESIGN POINT	TRIBUTARY BASINS	TRIBUTARY AREA (AC)	PEAK FLOWS (CFS)	
			Q5	Q100
<b>On-Site Basins</b>				
1, 1A	A	6.01	17.43	37.76
2, 2A	B	1.99	7.13	14.83
9	C	1.08	0.04	3.31
3	D	1.49	4.26	10.20
4	E	1.76	6.32	13.20
5	F	2.14	7.68	16.04
6	G	0.45	0.95	2.63
7	H	0.52	1.23	3.10
8	I	0.68	1.99	4.69
10	J	0.28	1.05	2.14
<b>TOTAL</b>		<b>16.40</b>	<b>48.08</b>	<b>107.91</b>



# DETENTION BASIN STAGE-STORAGE TABLE BUILDER

*MHFD-Detention, Version 4.04 (February 2021)*




# DETENTION BASIN OUTLET STRUCTURE DESIGN

MHFD- Detention, Version 4.04 (February 2021)

Project: \_\_\_\_\_

Basin ID: \_\_\_\_\_



	Estimated Stage (ft)	Estimated Volume (ac-ft)	Outlet Type
Zone 1 (WQCV)	2.31	0.452	Orifice Plate
Zone 2 (EURV)	4.14	0.847	Orifice Plate
Zone 3 (100-year)	5.64	0.884	Weir&Pipe (Restrict)
<b>Total (all zones)</b>		<b>2.183</b>	

User Input: Orifice at Underdrain Outlet (typically used to drain WQCV in a Filtration BMP)

Underdrain Orifice Invert Depth =	N/A	ft (distance below the filtration media surface)
Underdrain Orifice Diameter =	N/A	inches

Calculated Parameters for Underdrain

Underdrain Orifice Area =	N/A	ft <sup>2</sup>
Underdrain Orifice Centroid =	N/A	feet

User Input: Orifice Plate with one or more orifices or Elliptical Slot Weir (typically used to drain WQCV and/or EURV in a sedimentation BMP)

Invert of Lowest Orifice =	0.00	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Orifice Plate =	4.15	ft (relative to basin bottom at Stage = 0 ft)
Orifice Plate: Orifice Vertical Spacing =	N/A	inches
Orifice Plate: Orifice Area per Row =	N/A	inches

Calculated Parameters for Plate

WO Orifice Area per Row =	N/A	ft <sup>2</sup>
Elliptical Half-Width =	N/A	feet
Elliptical Slot Centroid =	N/A	feet
Elliptical Slot Area =	N/A	ft <sup>2</sup>

User Input: Stage and Total Area of Each Orifice Row (numbered from lowest to highest)

	Row 1 (required)	Row 2 (optional)	Row 3 (optional)	Row 4 (optional)	Row 5 (optional)	Row 6 (optional)	Row 7 (optional)	Row 8 (optional)
Stage of Orifice Centroid (ft)	0.00	2.00						
Orifice Area (sq. inches)	3.50	9.00						

	Row 9 (optional)	Row 10 (optional)	Row 11 (optional)	Row 12 (optional)	Row 13 (optional)	Row 14 (optional)	Row 15 (optional)	Row 16 (optional)
Stage of Orifice Centroid (ft)								
Orifice Area (sq. inches)								

User Input: Vertical Orifice (Circular or Rectangular)

	Not Selected	Not Selected	
Invert of Vertical Orifice =		N/A	ft (relative to basin bottom at Stage = 0 ft)
Depth at top of Zone using Vertical Orifice =		N/A	ft (relative to basin bottom at Stage = 0 ft)
Vertical Orifice Diameter =		N/A	inches

Calculated Parameters for Vertical Orifice

	Not Selected	Not Selected	
Vertical Orifice Area =		N/A	ft <sup>2</sup>
Vertical Orifice Centroid =		N/A	feet

User Input: Overflow Weir (Dropbox with Flat or Sloped Gate and Outlet Pipe OR Rectangular/Trapezoidal Weir (and No Outlet Pipe))

	Zone 3 Weir	Not Selected	
Overflow Weir Front Edge Height, Ho =	4.15	N/A	ft (relative to basin bottom at Stage = 0 ft)
Overflow Weir Front Edge Length =	2.92	N/A	feet
Overflow Weir Gate Slope =	3.00	N/A	H:V
Horiz. Length of Weir Sides =	5.55	N/A	feet
Overflow Gate Type =	No Gate	N/A	
Debris Clogging % =	0%	N/A	%

Calculated Parameters for Overflow Weir

	Zone 3 Weir	Not Selected	
Height of Gate Upper Edge, Hi =	6.00	N/A	feet
Overflow Weir Slope Length =	5.85	N/A	feet
Gate Open Area / 100-yr Orifice Area =	13.34	N/A	
Overflow Gate Open Area w/o Debris =	17.08	N/A	ft <sup>2</sup>
Overflow Gate Open Area w/ Debris =	17.08	N/A	ft <sup>2</sup>

User Input: Outlet Pipe w/ Flow Restriction Plate (Circular Orifice, Restrictor Plate, or Rectangular Orifice)

	Zone 3 Restrictor	Not Selected	
Depth to Invert of Outlet Pipe =	0.27	N/A	ft (distance below basin bottom at Stage = 0 ft)
Outlet Pipe Diameter =	18.00	N/A	inches
Restrictor Plate Height Above Pipe Invert =	12.25		inches

Calculated Parameters for Outlet Pipe w/ Flow Restriction Plate

	Zone 3 Restrictor	Not Selected	
Outlet Orifice Area =	1.28	N/A	ft <sup>2</sup>
Outlet Orifice Centroid =	0.57	N/A	feet
Half-Central Angle of Restrictor Plate on Pipe =	1.94	N/A	radians

User Input: Emergency Spillway (Rectangular or Trapezoidal)

Spillway Invert Stage =	5.94	ft (relative to basin bottom at Stage = 0 ft)
Spillway Crest Length =	30.00	feet
Spillway End Slopes =	4.00	H:V
Freeboard above Max Water Surface =	0.00	feet

Calculated Parameters for Spillway

Spillway Design Flow Depth =	0.70	feet
Stage at Top of Freeboard =	6.64	feet
Basin Area at Top of Freeboard =	0.72	acres
Basin Volume at Top of Freeboard =	2.87	acre-ft




## Routed Hydrograph Results

*The user can override the default CUHP hydrographs and runoff volumes by entering new values in the Inflow Hydrographs table (Columns W through AF).*

	WQCV	EURV	2 Year	5 Year	10 Year	25 Year	50 Year	100 Year	500 Year
Design Storm Return Period									
One-Hour Rainfall Depth (in)	N/A	N/A	1.06	1.43	1.66	1.68	2.26	2.60	3.07
CUHP Runoff Volume (acre-ft)	0.452	1.299	1.151	1.663	1.990	2.035	2.873	3.385	4.069
Inflow Hydrograph Volume (acre-ft)	N/A	N/A	1.151	1.663	1.990	2.035	2.873	3.385	4.069
CUHP Predevelopment Peak Q (cfs)	N/A	N/A	1.5	5.5	7.7	9.7	17.0	22.2	28.3
OPTIONAL Override Predevelopment Peak Q (cfs)	N/A	N/A							
Predevelopment Unit Peak Flow, q (cfs/acre)	N/A	N/A	0.09	0.33	0.46	0.59	1.03	1.34	1.71
Peak Inflow Q (cfs)	N/A	N/A	19.5	27.8	32.2	33.9	47.6	57.0	68.3
Peak Outflow Q (cfs)	0.3	0.7	0.6	1.6	3.4	3.6	10.6	14.6	28.4
Ratio Peak Outflow to Predevelopment Q	N/A	N/A	N/A	0.3	0.4	0.4	0.6	0.7	1.0
Structure Controlling Flow	Plate	Plate	Plate	Overflow Weir 1	Overflow Weir 1	Overflow Weir 1	Overflow Weir 1	Outlet Plate 1	Spillway
Max Velocity through Gate 1 (fps)	N/A	N/A	N/A	0.1	0.2	0.2	0.6	0.8	0.8
Max Velocity through Gate 2 (fps)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Time to Drain 97% of Inflow Volume (hours)	40	54	53	57	57	57	54	52	50
Time to Drain 99% of Inflow Volume (hours)	43	59	58	63	63	63	62	61	60
Maximum Ponding Depth (ft)	2.31	4.14	3.68	4.52	4.85	4.87	5.51	5.93	6.22
Area at Maximum Ponding Depth (acres)	0.35	0.54	0.51	0.56	0.59	0.59	0.63	0.67	0.69
Maximum Volume Stored (acre-ft)	0.454	1.301	1.056	1.510	1.694	1.706	2.096	2.369	2.565

# DETENTION BASIN OUTLET STRUCTURE DESIGN

*MHFD-Detention, Version 4.04 (February 2021)*



S-A-V-D Chart Axis Override	X-axis	Left Y-Axis	Right Y-Axis
minimum bound			
maximum bound			

# DETENTION BASIN OUTLET STRUCTURE DESIGN

Outflow Hydrograph Workbook Filename: \_\_\_\_\_

## Inflow Hydrographs

The user can override the calculated inflow hydrographs from this workbook with inflow hydrographs developed in a separate program.

Time Interval	SOURCE	WQCV [cfs]	EURV [cfs]	2 Year [cfs]	5 Year [cfs]	10 Year [cfs]	25 Year [cfs]	50 Year [cfs]	100 Year [cfs]	500 Year [cfs]
5.00 min	0:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	0:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.31	0.15	0.84
	0:15:00	0.00	0.00	1.94	3.91	4.83	2.39	4.43	4.55	5.90
	0:20:00	0.00	0.00	7.81	11.36	13.49	6.88	10.21	11.43	14.21
	0:25:00	0.00	0.00	16.84	24.71	29.51	15.34	22.44	24.97	30.81
	0:30:00	0.00	0.00	19.48	27.80	32.18	31.50	44.92	51.10	61.47
	0:35:00	0.00	0.00	17.48	24.50	28.23	33.85	47.62	57.04	68.25
	0:40:00	0.00	0.00	15.15	20.81	23.99	31.48	44.02	52.54	62.80
	0:45:00	0.00	0.00	12.37	17.42	20.34	27.19	37.98	46.67	55.75
	0:50:00	0.00	0.00	10.18	14.74	16.93	23.76	33.12	40.49	48.34
	0:55:00	0.00	0.00	8.76	12.65	14.80	19.53	27.25	34.19	40.83
	1:00:00	0.00	0.00	7.75	11.11	13.23	16.72	23.36	30.07	35.91
	1:05:00	0.00	0.00	6.82	9.72	11.75	14.56	20.36	26.97	32.21
	1:10:00	0.00	0.00	5.54	8.44	10.37	12.08	16.92	21.67	25.91
	1:15:00	0.00	0.00	4.48	7.08	9.25	9.93	13.93	17.18	20.57
	1:20:00	0.00	0.00	3.80	6.05	8.06	7.82	10.96	12.73	15.26
	1:25:00	0.00	0.00	3.44	5.49	6.96	6.43	9.01	9.68	11.62
	1:30:00	0.00	0.00	3.25	5.16	6.22	5.34	7.48	7.80	9.38
	1:35:00	0.00	0.00	3.15	4.94	5.70	4.63	6.48	6.64	7.99
	1:40:00	0.00	0.00	3.08	4.39	5.33	4.15	5.80	5.84	7.02
	1:45:00	0.00	0.00	3.02	3.96	5.07	3.84	5.36	5.30	6.37
	1:50:00	0.00	0.00	2.98	3.66	4.89	3.62	5.05	4.92	5.91
	1:55:00	0.00	0.00	2.57	3.43	4.61	3.48	4.84	4.66	5.61
	2:00:00	0.00	0.00	2.25	3.16	4.12	3.38	4.71	4.55	5.47
	2:05:00	0.00	0.00	1.64	2.30	2.97	2.46	3.41	3.31	3.98
	2:10:00	0.00	0.00	1.15	1.62	2.09	1.73	2.41	2.34	2.82
	2:15:00	0.00	0.00	0.80	1.12	1.46	1.22	1.69	1.66	1.99
	2:20:00	0.00	0.00	0.55	0.76	1.00	0.84	1.16	1.14	1.37
	2:25:00	0.00	0.00	0.37	0.50	0.67	0.56	0.78	0.77	0.92
	2:30:00	0.00	0.00	0.24	0.33	0.45	0.38	0.53	0.52	0.63
	2:35:00	0.00	0.00	0.14	0.21	0.27	0.24	0.34	0.33	0.40
	2:40:00	0.00	0.00	0.07	0.11	0.14	0.13	0.18	0.18	0.22
	2:45:00	0.00	0.00	0.03	0.05	0.05	0.06	0.08	0.07	0.09
	2:50:00	0.00	0.00	0.01	0.01	0.01	0.01	0.02	0.01	0.02
	2:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:05:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:10:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:15:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:20:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:25:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:30:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:35:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:40:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:45:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:50:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	5:55:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6:00:00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00



ATTACHMENT 4: PAGES FROM APPROVED *PHASE III DRAINAGE STUDY, PROJECT MAJESTIC (DECEMBER 1994)*



**MARTIN/MARTIN**

---

---

PHASE III DRAINAGE STUDY  
PROJECT MAJESTIC  
DOUGLAS COUNTY, COLORADO  
OCTOBER 1994  
REV. DECEMBER 1994

DOUGLAS COUNTY  
FEB 24 1995  
Department of Public Works

DV 94-184

## II DESIGN CRITERIA

On-site flows were calculated using the Rational Method as described in the Urban Drainage Flood Control District's "Urban Storm Drainage Manual, Volume 1", revised May 1984. Runoff flows were calculated for the 5-year and 100-year design storms. A minimum time of concentration ( $T_c$ ) of five minutes was used when applicable. Street and gutter capacity was done in accordance with Douglas County Drainage Criteria Manual. It was determined that no off-site flows would enter the site. Detention will be provided on-site. The proposed detention pond will release into a proposed swale that flows to an existing detention pond that was designed and detailed in a previous Drainage Study entitled "Parkway Master Drainage Study", prepared by Costin Engineering Company, July 1984.

concentration (Tc) of 5:00 minutes with a minor and major runoff flow of 7.35 cfs and 14.22 cfs. Runoff flows east where it is captured by roof drains and routed through pipes to the detention pond. Basin G has a time of concentration (Tc) of 7.75 minutes with a minor and major flow of 1.68 cfs and 2.24 cfs. Runoff flows southeast to Inlet HH (Design Point 6) which is located in a sump on the southwest side of Basin G. Runoff captured then flows through pipes to the detention pond. Basin H has a concentration time (Tc) of 7.58 minutes with minor and major runoff flow of 2.16 cfs and 2.89 cfs. Runoff flows north to Inlet GG (Design Point 7) which is located in a sump on the north side of Basin H. Runoff captured then flows through pipes to the detention pond. Basin I has a time of concentration (Tc) of 5:00 minutes with a minor and major runoff flow of 2.65 cfs and 5.58 cfs. Runoff flows north to Inlet FF (Design Point 8) which is located in a sump on the north side of Basin I. Runoff captured then flows the detention pond. Basin J has a concentration time (Tc) of 5.00 minutes with a minor and major runoff flow of 1.23 cfs and 2.34 cfs. Runoff flows undetained northeast to South Yosemite Street.

Detention for the site will be provided on the site. It was determined that the detention volume needed for the 10-year storm was 1.22 acre ft. and 2.08 acre ft. for the 100-year storm. The detention pond will release at a rate of 3.61 cfs for the minor storm and 14.47 cfs for the major storm.

None of the developed or historic flows outlined above exceed the street/gutter capacities outlined in the Douglas County Storm Drainage and Technical Criteria Manual (see Appendix B).

TABLE A  
PROPOSED BASIN SUMMARY

<u>BASIN DESIGNATION</u>	<u>AREA (AC)</u>	<u>C<sub>5</sub></u>	<u>C<sub>100</sub></u>	<u>T<sub>c</sub> (MIN)</u>	<u>Q<sub>5</sub> (CFS)</u>	<u>Q<sub>100</sub> (CFS)</u>
A	6.01	.81	.87	7.27	21.92	40.10
B	1.99	.82	.88	5.00	8.00	15.76
C	1.08	.01	.20	7.33	0.48	1.75
D	1.49	.67	.75	5.00	4.90	10.08
E	1.76	.85	.90	5.00	7.35	14.22
F	1.76	.85	.90	5.00	7.35	14.22
G	0.45	.51	.62	7.75	1.68	2.24
H	0.64	.46	.58	7.58	2.16	2.89
I	0.88	.61	.71	5.00	2.65	5.58
J	0.28	.88	.93	5.00	1.23	2.34

TABLE B  
DESIGN POINT SUMMARY

<u>DESIGN POINT</u>	<u>CONTRIBUTING BASINS</u>	<u>AREA (AC)</u>	<u>Q<sub>5</sub> (CFS)</u>	<u>Q<sub>100</sub> (CFS)</u>
1A	A	6.01	2.50	2.50
1	A	6.01	19.42	37.60
2A	B	1.99	2.50	2.50
2	B	1.99	5.50	13.26
3	D	1.49	4.90	10.08
4	E	1.76	7.35	14.22
5	F	1.76	7.35	14.22
6	G	0.45	1.68	2.24
7	H	0.64	2.16	2.89
8	I	0.88	2.65	5.58

TABLE C  
INLET DESIGN INFORMATION

<u>INLET</u>	<u>DESIGN STREET POINT</u>	<u>SLOPE %</u>	<u>INLET SIZE</u>	<u>INLET CAP</u>	<u>GUTTER CAP</u>	<u>Q<sub>CO</sub> (PREV.)</u>	<u>Q<sub>ST</sub></u>	<u>Q<sub>D</sub></u>	<u>Q<sub>I</sub></u>	<u>Q<sub>CO</sub></u>	<u>DESIGN STORM</u>
AA	2	SUMP	5' TYPE R	12.0	1.0' POND	5.50	5.50	5.50	5.50	0	5 YR
BB	2A	SUMP	SINGLE NO.16	2.5	.17' POND	0	8.00	8.00	2.50	5.50	5 YR
CC	1	SUMP	15' TYPE R	38.0	1.0' POND	19.42	19.42	19.42	6.06	0	5 YR
DD	1A	SUMP	SINGLE NO.16	2.5	.17' POND	0	21.92	21.92	8.88	19.42	5 YR
EE	3	SUMP	10' TYPE R	10.50	0.5' POND	0	4.90	4.90	4.90	0	5 YR
FF	8	SUMP	10' TYPE R	10.50	0.5' POND	0	2.65	2.65	2.65	0	5 YR
GG	7	SUMP	5' TYPE R	12.0	1.0' POND	0	2.16	2.16	2.16	0	5 YR
HH	6	SUMP	5' TYPE R	12.0	1.0' POND	0	1.68	1.68	1.68	0	5 YR
AA	2	SUMP	5' TYPE R	12.0	1.0' POND	13.26	13.26	13.26	13.26	0	100 YR
BB	2A	SUMP	SINGLE NO.16	2.5	.17' POND	0	15.76	15.76	2.50	13.26	100 YR
CC	1	SUMP	15' TYPE R	38.0	1.0' POND	37.60	37.60	37.60	37.60	0	100 YR
DD	1A	SUMP	SINGLE NO.16	2.5	.17' POND	0	40.10	40.10	2.50	37.60	100 YR
EE	3	SUMP	10' TYPE R	10.50	0.5' POND	0	10.08	10.08	10.08	0	100 YR
FF	8	SUMP	10' TYPE R	10.50	0.5' POND	0	5.58	5.58	5.58	0	100 YR
GG	7	SUMP	5' TYPE R	12.0	1.0' POND	0	2.89	2.89	2.89	0	100 YR
HH	6	SUMP	5' TYPE R	12.0	1.0' POND	0	2.24	2.24	2.24	0	100 YR

# STANDARD FORM SF-2

## TIME OF CONCENTRATION

SUBDIVISION MAJESTIC (TANDY)

REV 12-19-84

CALCULATED BY D. LOVATO

DATE 8-19-94

$$t_c = t_l + t_t$$

SUB-BASIN DATA			INITIAL/OVERLAND TIME ( $t_i$ )			TRAVEL TIME ( $t_t$ )				$t_c$ CHECK (URBANIZED BASINS)		FINAL $t_c$	REMARKS
DESIG:	$C_s$	AREA $A_c$	LENGTH Ft	SLOPE %	$t_i$ Min	LENGTH Ft	SLOPE %	VEL. FPS	$t_t$ Min	TOTAL LENGTH Ft	$t_c = L/180 + 10$ Min	Min	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	
A	0.81	6.01	30	2.00	2.27	720	1.50	2.40	5.00	750	14.17	7.27	
B	0.82	1.99	-	-	-	380	2.45	3.30	2.11	380	12.11	5.00	USE MIN TC = 5.0
C	0.30	1.08	60	2.00	5.98	300	3.33	3.70	1.35	360	12.00	7.33	
D	0.67	1.49	40	15.00	1.98	330	1.30	2.30	2.39	370	12.06	5.00	USE MIN TC = 5.0
E	0.85	1.76	-	-	-	200	2.00	2.90	1.15	200	11.11	5.00	USE MIN TC = 5.0
F	0.85	1.76	-	-	-	200	2.00	2.90	1.15	200	11.11	5.00	USE MIN TC = 5.0
G	0.51	0.45	55	2.00	6.25	135	0.50	1.50	1.50	190	11.06	7.75	
H	0.46	0.64	55	2.00	6.25	160	1.00	2.00	1.33	215	11.19	7.58	
I	0.61	0.88	35	6.67	2.77	190	2.34	3.20	0.99	225	11.25	5.00	USE MIN TC = 5.0
J	0.88	0.28	-	-	-	230	4.00	4.00	0.96	230	11.27	5.00	USE MIN TC = 5.0

CALCULATED BY D LOVATO  
 DATE 8-19-94 REV 12-19-94  
 CHECKED BY \_\_\_\_\_

**STANDARD FORM SF-3**  
**STORM DRAINAGE SYSTEM DESIGN**  
**(RATIONAL METHOD PROCEDURE)**

JOB NO. \_\_\_\_\_  
 PROJECT MAJESTIC CTANL  
 DESIGN STORM 5YR

STREET	DESIGN POINT	DIRECT RUNOFF							TOTAL RUNOFF				STREET		PIPE		TRAVEL TIME			REMARKS	
		AREA DESIGN	AREA (AC)	RUNOFF COEFF	$T_c$ (MIN)	C-A (AC)	I IN/HR	Q (CFS)	$T_c$ (MIN)	$Z(C-A)$ (AC)	I (IN/HR)	Q (CFS)	SLOPE (%)	STREET FLOW (CFS)	DESIGN FLOW (CFS)	SLOPE (%)	PIPE SIZE	LENGTH (FT)	VELOCITY (FPS)		$T_c$ (MIN)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	(21)	(22)
1	A	1	6.01	.81	7.27	4.87	4.50	21.92													
2	B	2	1.99	.82	5.00	1.63	4.90	8.00													
3	C		1.08	.01	7.33	.01	4.48	0.48													
4	D	3	1.49	.67	5.00	1.00	4.90	4.90													
5	E	4	1.76	.85	5.00	1.50	4.90	7.35													
6	F	5	1.76	.85	5.00	1.50	4.90	7.35													
7	G	6	0.45	.51	7.75	.23	7.30	1.68													
8	H	7	0.64	.46	7.58	.29	7.35	2.16													
9	I	8	0.88	.61	5.00	.54	4.90	2.65													
10	J		0.28	.88	5.00	.25	4.90	1.23													
11																					



CALCULATED BY D LOVATO

DATE 8-19-94 REV 12-19-94

CHECKED BY \_\_\_\_\_

**STANDARD FORM SF-3**

**STORM DRAINAGE SYSTEM DESIGN  
(RATIONAL METHOD PROCEDURE)**

JOB NO \_\_\_\_\_

PROJECT MAJESTIC TAIL

DESIGN STORM 100 YR

BASIN	DESIGN POINT	DIRECT RUNOFF								TOTAL RUNOFF				STREET		PIPE			TRAVEL TIME			REMARKS
		AREA DESIGN	AREA (AC)	RUNOFF COEFF	$t_c$ (MIN)	C.A (AC)	I IN/HR	Q (CFS)	$t_c$ (MIN)	$\Sigma(C.A)$ (AC)	I (IN/HR)	Q (CFS)	SLOPE (%)	STREET FLOW(CFS)	DESIGN FLOW (CFS)	SLOPE (%)	PIPE SIZE	LENGTH (FT)	VELOCITY (FPS)	$t_t$ (MIN)		
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	(21)	(22)	
1	A	1	6.01	.87	7.27	5.23	8.05	40.10														
2	B	2	1.99	.88	5.00	1.75	9.00	15.76														
3	C		1.08	.20	7.33	.22	7.95	1.75														
4	D	3	1.49	.75	5.00	1.12	9.00	10.08														
5	E	4	1.76	.90	5.00	1.58	9.00	14.22														
6	F	5	1.76	.90	5.00	1.58	9.00	14.22														
7	G	6	0.45	.62	7.75	.29	7.75	2.24														
8	H	7	0.64	.58	7.58	.37	7.80	2.89														
9	I	8	0.88	.71	5.00	.62	9.00	5.58														
10	J		0.28	.93	5.00	.26	9.00	2.34														
11																						

BASIN A

$$A_T = 6.01 \text{ AC}$$

$$A_{sw} = 0.30 \text{ AC} \quad C_s = 0.87 \quad C_{100} = 0.89$$

$$A_L = 0.44 \text{ AC} \quad C_s = 0.01 \quad C_{100} = 0.20$$

$$A_p = 5.27 \text{ AC} \quad C_s = 0.88 \quad C_{100} = 0.93$$

$$C_s = \frac{(0.87)(0.30) + (0.01)(0.44) + (0.88)(5.27)}{6.01} = \underline{\underline{0.81}}$$

$$C_{100} = \frac{(0.89)(0.30) + (0.20)(0.44) + (0.93)(5.27)}{6.01} = \underline{\underline{0.87}}$$

BASIN B

$$A_T = 1.99 \text{ AC}$$

$$A_{sw} = 0.05 \text{ AC} \quad C_s = 0.87 \quad C_{100} = 0.89$$

$$A_L = 0.12 \text{ AC} \quad C_s = 0.01 \quad C_{100} = 0.20$$

$$A_p = 1.82 \text{ AC} \quad C_s = 0.88 \quad C_{100} = 0.93$$

$$C_s = \frac{(0.87)(0.05) + (0.01)(0.12) + (0.88)(1.82)}{1.99} = \underline{\underline{0.82}}$$

$$C_{100} = \frac{(0.89)(0.05) + (0.20)(0.12) + (0.93)(1.82)}{1.99} = \underline{\underline{0.88}}$$

BASIN C

$$A_T = 1.08 \text{ AC}$$

$$A_L = 1.08 \text{ AC}$$

$$A_P = 0.00 \text{ AC}$$

$$C_5 = 0.01$$

$$C_{100} = 0.20$$

$$C_5 = 0.88$$

$$C_{100} = 0.93$$

$$C_5 = \frac{(0.01)(1.08)}{1.08} = \underline{\underline{0.01}}$$

$$C_{100} = \frac{(0.20)(1.08)}{1.08} = \underline{\underline{0.20}}$$

BASIN D

$$A_T = 1.49 \text{ AC}$$

$$A_L = 0.36 \text{ AC}$$

$$A_P = 1.13 \text{ AC}$$

$$C_5 = 0.01$$

$$C_{100} = 0.20$$

$$C_5 = 0.88$$

$$C_{100} = 0.93$$

$$C_5 = \frac{(0.01)(0.36) + (0.88)(1.13)}{1.49} = \underline{\underline{0.67}}$$

$$C_{100} = \frac{(0.20)(0.36) + (0.93)(1.13)}{1.49} = \underline{\underline{0.75}}$$

BASIN E

$$A_T = 1.76 \text{ AC}$$

$$A_R = 1.76 \text{ AC}$$

$$\underline{\underline{C_5 = 0.85}}$$

$$\underline{\underline{C_{100} = 0.90}}$$

BASIN F

$$A_T = 1.76 \text{ AC}$$

$$A_R = 1.76 \text{ AC}$$

$$\underline{\underline{C_5 = 0.85}}$$

$$\underline{\underline{C_{100} = 0.90}}$$

BASIN G

$A_T = 0.45 \text{ AC}$

$A_L = 0.19 \text{ AC}$

$C_S = 0.01$

$C_{100} = 0.20$

$A_P = 0.23 \text{ AC}$

$C_S = 0.88$

$C_{100} = 0.93$

$A_{SW} = 0.03 \text{ AC}$

$C_S = 0.87$

$C_{100} = 0.89$

$$C_S = \frac{(0.01)(0.19) + (0.88)(0.23) + (0.87)(0.03)}{0.45} = \underline{\underline{0.51}}$$

$$C_{100} = \frac{(0.20)(0.19) + (0.93)(0.23) + (0.89)(0.03)}{0.45} = \underline{\underline{0.62}}$$

BASIN H

$A_T = 0.64 \text{ AC}$

$A_L = 0.31 \text{ AC}$

$C_S = 0.01$

$C_{100} = 0.20$

$A_P = 0.33 \text{ AC}$

$C_S = 0.88$

$C_{100} = 0.93$

$$C_S = \frac{(0.01)(0.31) + (0.88)(0.33)}{0.64} = \underline{\underline{0.46}}$$

$$C_{100} = \frac{(0.20)(0.31) + (0.93)(0.33)}{0.64} = \underline{\underline{0.58}}$$

BASIN I

$A_T = 0.88 \text{ AC}$

$A_L = 0.27 \text{ AC}$

$C_S = 0.01$

$C_{100} = 0.20$

$A_P = 0.61 \text{ AC}$

$C_S = 0.88$

$C_{100} = 0.93$

$$C_S = \frac{(0.01)(0.27) + (0.88)(0.61)}{0.88} = \underline{\underline{0.61}}$$

$$C_{100} = \frac{(0.20)(0.27) + (0.93)(0.61)}{0.88} = \underline{\underline{0.71}}$$

BASIN J

$C_S = 0.88$

$C_{100} = 0.93$

INLET DD (DESIGN POINT 1A)

TOTAL FLOW IS RUNOFF TO DESIGN POINT 1.  
INLET IN PAN WILL CAPTURE MINIMAL FLOW

$$Q_5 = 21.92 \quad \text{CAN POINT TO PAN DEPTH OF 0.17 FT}$$

$$Q_{100} = 40.10$$

USE TYPE 16 COMBINATION

$$Q_A = 2.5 \text{ CFS} *$$

$$Q_{CO5} = 21.92 - 2.5 = 19.42 \text{ CFS}$$

$$Q_{CO100} = 40.10 - 2.5 = 37.60 \text{ CFS}$$

CARRY OVER TO D.P. 1 INLET CC

INLET CC (DESIGN POINT 1)

CARRY OVER FLOW FROM INLET DD

$$Q_5 = 19.42 \text{ CFS}$$

$$Q_{100} = 37.60 \text{ CFS}$$

PONDING DEPTH = 1.0' (SUMP CONDITION)

USE TYPE 16

$$Q_A = 2.5 \text{ CFS}$$

$$Q_{INS} = 19.42 \text{ CFS} *$$

$$Q_{IN100} = 37.60 \text{ CFS} *$$

NO CARRYOVER

FLOW @ ST MH 3

$$\rightarrow Q_5 = 19.42 + 2.50 = 21.92 \text{ CFS}$$

$$\rightarrow Q_{100} = 37.60 + 2.50 = 40.10 \text{ CFS}$$

INLET BB (DESIGN POINT 2A)

TOTAL FLOW IS RUNOFF TO DESIGN POINT 2A  
INLET IN PAN WILL CAPTURE MINIMAL FLOW

$$Q_5 = 8.00 \text{ CFS} \quad \text{CAN POND TO PAN DEPTH OF 0.17'}$$

$$Q_{100} = 15.76 \text{ CFS}$$

USE TYPE 1G COMBINATION

$$Q_A = 2.5 \text{ CFS} *$$

$$Q_{C05} = 8.00 - 2.5 = 5.50 \text{ CFS}$$

$$Q_{C0100} = 15.76 - 2.5 = 13.26 \text{ CFS}$$

CARRY OVER TO D.P. 2 INLET AA

INLET AA (DESIGN POINT 2)

CARRY OVER FLOW FROM INLET BB

$$Q_5 = 5.50 \text{ CFS}$$

$$Q_{100} = 13.26 \text{ CFS}$$

PONDING DEPTH = 1.0' (SUMP CONDITION)

USE 5' TYPE R

$$Q_A = 12.5 \text{ CFS}$$

$$Q_{15} = 2.5 \text{ CFS} *$$

$$Q_{100} = 13.26 \text{ CFS} *$$

Flow e ST. MH 1

$$\rightarrow Q_5 = 21.92 + 2.5 + 5.50 = 29.92$$

$$\rightarrow Q_{100} = 40.10 + 2.5 + 13.26 = 55.86$$

FLOW INTO POND ←

INLET EE (DESIGN POINT 3)

$$Q_5 = 4.90 \text{ CFS}$$

$$Q_{100} = 10.08 \text{ CFS}$$

PONDING DEPTH = 0.5' (SUMP CONDITION)  
HEIGHT OF CURB.

USE 10' TYPE R

$$Q_A = 10.50 \text{ CFS}$$

$$Q_{INS} = 4.90 \text{ CFS} *$$

$$Q_{IN100} = 10.08 \text{ CFS} *$$

NO CARRY OVER

FLOW @ ST MH 4

$$Q_5 = 13.85 + 4.90 + 7.35 = 26.10 \text{ CFS}$$

$$Q_{100} = 24.93 + 10.08 + 14.22 = 49.23 \text{ CFS}$$

FLOW INTO  
POND ←

INLET FF (DESIGN POINT 8)

$$Q_5 = 2.65 \text{ CFS}$$

$$Q_{100} = 5.58 \text{ CFS}$$

PONDING DEPTH = 0.5' (SUMP CONDITION)  
HEIGHT OF CURB

USE 10' TYPE R

$$Q_A = 11.20 \text{ CFS}$$

$$Q_{INS} = 2.65 \text{ CFS} *$$

$$Q_{IN100} = 5.58 \text{ CFS} *$$

NO CARRY OVER

FLOW @ ST MH 7

$$\rightarrow Q_5 = 11.20 + 2.65 = 13.85 \text{ CFS}$$

$$\rightarrow Q_{100} = 19.35 + 5.58 = 24.93 \text{ CFS}$$

INLET GG (DESIGN POINT 7)

$$Q_5 = 2.16 \text{ CFS}$$

$$Q_{100} = 2.89 \text{ CFS}$$

PONDING DEPTH = 1.0' (SUMP CONDITION)

USE 5' TYPE R

$$Q_A = 12.0 \text{ CFS}$$

$$Q_{INS} = 2.16 \text{ CFS} *$$

$$Q_{IN100} = 2.89 \text{ CFS} *$$

NO CARRY OVER

FLOW @ ST MH 9

$$\rightarrow Q_5 = 5.36 + 2.16 + 3.68 = 11.20 \text{ CFS}$$

$$\rightarrow Q_{100} = 9.35 + 2.89 + 7.11 = 19.35 \text{ CFS}$$

INLET HH (DESIGN POINT 6)

$$Q_5 = 1.68 \text{ CFS}$$

$$Q_{100} = 2.24 \text{ CFS}$$

PONDING DEPTH = 1.0 (SUMP CONDITION)

USE 5' TYPE R

$$Q_A = 12.0 \text{ CFS}$$

$$Q_{INS} = 1.68 \text{ CFS} *$$

$$Q_{IN100} = 2.24 \text{ CFS} *$$


NO CARRY OVER

FLOW @ ST MH 10

$$\rightarrow Q_5 = 1.68 + 3.68 = 5.36 \text{ CFS}$$

$$\rightarrow Q_{100} = 2.24 + 7.11 = 9.35 \text{ CFS}$$





=====

REPORT OF STORM SEWER SYSTEM DESIGN

USING UDSEWER-MODEL July-2-1993  
DEVELOPED  
BY

JAMES C.Y. GUO ,PHD, PE  
DEPARTMENT OF CIVIL ENGINEERING, UNIVERSITY OF COLORADO AT DENVER  
IN COOPERATION WITH  
URBAN DRAINAGE AND FLOOD CONTROL DISTRICT  
DENVER, COLORADO

=====

\*\*\* EXECUTED BY Martin-Martin.....  
ON DATA 01-09-1995 AT TIME 10:06:05

\*\*\* PROJECT TITLE :

MAJESTIC TANDY STORM LINE A

\*\*\* RETURN PERIOD OF FLOOD IS 5 YEARS

RAINFALL INTENSITY FORMULA IS GIVEN

\*\*\* SUMMARY OF SUBBASIN RUNOFF PREDICTIONS

-----

MANHOLE ID NUMBER	BASIN AREA * C	TIME OF CONCENTRATION			RAIN I INCH/HR	PEAK FLOW CFS
		OVERLAND To (MIN)	GUTTER Tf (MIN)	BASIN Tc (MIN)		
1.00	1.80	0.00	0.00	0.00	4.75	8.55
2.00	6.00	0.00	0.00	0.00	4.75	28.49
4.00	6.00	0.00	0.00	29.69	2.21	13.26
5.00	6.00	0.00	0.00	0.00	4.75	28.49
6.00	6.00	0.00	0.00	0.00	4.75	28.49
7.00	6.00	0.00	0.00	0.00	4.75	28.49
8.00	6.00	0.00	0.00	14.43	3.24	19.42

-----

THE SHORTEST DESIGN RAINFALL DURATION IS FIVE MINUTES

FOR RURAL AREA, BASIN TIME OF CONCENTRATION =>10 MINUTES

FOR URBAN AREA, BASIN TIME OF CONCENTRATION =>5 MINUTES

AT THE 1ST DESIGN POINT, TC <=(10+TOTAL LENGTH/180) IN MINUTES

WHEN WEIGHTED RUNOFF COEFF=> .2 , THE BASIN IS CONSIDERED TO BE URBANIZED  
WHEN TO+TF<>TC, IT INDICATES THE ABOVE DESIGN CRITERIA SUPERCEDES COMPUTATIONS

\*\*\* SUMMARY OF HYDRAULICS AT MANHOLES

MANHOLE ID NUMBER	CNTRBTING AREA * C	RAINFALL DURATION MINUTES	RAINFALL INTENSITY INCH/HR	DESIGN PEAK FLOW CFS	GROUND ELEVATION FEET	WATER ELEVATION FEET	COMMENTS
1.00	0.00	0.00	0.00	29.90	11.60	8.21	OK
2.00	0.00	29.87	0.00	29.90	17.76	9.15	OK
4.00	6.00	29.69	2.21	13.26	16.61	9.99	OK
5.00	0.00	15.44	0.00	21.92	19.49	9.92	OK
6.00	0.00	14.80	0.00	21.92	17.60	11.22	OK
7.00	0.00	14.56	0.00	21.92	16.07	11.77	OK
8.00	6.00	14.43	3.24	19.42	15.00	12.09	OK

OK MEANS WATER ELEVATION IS LOWER THAN GROUND ELEVATION

\*\*\* SUMMARY OF SEWER HYDRAULICS

NOTE: THE GIVEN FLOW DEPTH-TO-SEWER SIZE RATIO= .8

SEWER ID NUMBER	MAMHOLE UPSTREAM ID NO.	NUMBER DNSTREAM ID NO.	SEWER SHAPE	REQUIRED DIA(HIGH) (IN) (FT)	SUGGESTED DIA(HIGH) (IN) (FT)	EXISTING DIA(HIGH) (IN) (FT)	WIDTH (FT)
21.00	2.00	1.00	ROUND	31.20	33.00	36.00	0.00
42.00	4.00	2.00	ROUND	23.00	24.00	24.00	0.00
52.00	5.00	2.00	ROUND	27.78	30.00	36.00	0.00
65.00	6.00	5.00	ROUND	27.78	30.00	36.00	0.00
76.00	7.00	6.00	ROUND	27.78	30.00	36.00	0.00
87.00	8.00	7.00	ROUND	26.54	27.00	36.00	0.00

DIMENSION UNITS FOR ROUND AND ARCH SEWER ARE IN INCHES

DIMENSION UNITS FOR BOX SEWER ARE IN FEET

REQUIRED DIAMETER WAS DETERMINED BY SEWER HYDRAULIC CAPACITY.

SUGGESTED DIAMETER WAS DETERMINED BY COMMERCIALY AVAILABLE SIZE.

FOR A NEW SEWER, FLOW WAS ANALYZED BY THE SUGGESTED SEWER SIZE; OTHERWISE, EXISITNG SIZE WAS USED

SEWER ID NUMBER	DESIGN FLOW Q CFS	FLOW FULL Q CFS	NORMAL DEPTH FEET	NORAML VLCITY FPS	CRITIC DEPTH FEET	CRITIC VLCITY FPS	FULL VLCITY FPS	FROUDE NO.	COMMENT
21.0	29.9	43.9	1.82	6.68	1.77	6.90	4.23	0.95	V-OK
42.0	13.3	14.9	1.47	5.36	1.31	13.74	4.22	0.80	V-OK
52.0	21.9	43.9	1.50	6.21	1.54	3.64	3.10	1.01	V-OK
65.0	21.9	43.9	1.50	6.21	1.54	6.02	3.10	1.01	V-OK
76.0	21.9	43.9	1.50	6.21	1.54	6.02	3.10	1.01	V-OK
87.0	19.4	43.9	1.40	6.02	1.47	6.37	2.75	1.02	V-OK

FROUDE NUMBER=0 INDICATES THAT A PRESSURED FLOW OCCURS

SEWER ID NUMBER	SLOPE %	INVERT ELEVATION		BURIED DEPTH		COMMENTS
		UPSTREAM (FT)	DNSTREAM (FT)	UPSTREAM (FT)	DNSTREAM (FT)	
21.00	0.50	7.28	6.60	7.48	2.00	OK
42.00	0.50	7.67	7.39	6.94	8.38	OK
52.00	0.50	8.38	7.38	8.11	7.38	OK
65.00	0.50	9.68	8.48	4.92	8.01	OK
76.00	0.50	10.23	9.78	2.84	4.82	OK
87.00	0.50	10.57	10.34	1.43	2.73	NO

OK MEANS BURIED DEPTH IS GREATER THAN REQUIRED SOIL COVER OF 1.5 FEET

\*\*\* SUMMARY OF HYDRAULIC GRADIENT LINE ALONG SEWERS

SEWER ID NUMBER	SEWER LENGTH FEET	SURCHARGED LENGTH FEET	CROWN ELEVATION		WATER ELEVATION		FLOW CONDITION
			UPSTREAM FEET	DNSTREAM FEET	UPSTREAM FEET	DNSTREAM FEET	
21.00	136.00	0.00	10.28	9.60	9.15	8.21	SUBCR
42.00	57.00	57.00	9.67	9.39	9.99	9.15	PRSS'ED
52.00	200.00	0.00	11.38	10.38	9.92	9.15	JUMP
65.00	240.00	0.00	12.68	11.48	11.22	9.92	JUMP
76.00	89.00	0.00	13.23	12.78	11.77	11.22	JUMP
87.00	47.00	0.00	13.57	13.34	12.09	11.77	JUMP

PRSS'ED=PRESSURED FLOW; JUMP=POSSIBLE HYDRAULIC JUMP; SUBCR=SUBCRITICAL FLOW

\*\*\* SUMMARY OF ENERGY GRADIENT LINE ALONG SEWERS

SEWER ID NO	UPST MANHOLE ID NO.	SEWER ENERGY ELEV FT	SEWER FRCTION FT	BEND K COEF	JUNCTURE LOSSES				DOWNST MANHOLE ID	ENERGY FT
					BEND LOSS FT	LATERAL K COEF	LATERAL LOSS FT	LATERAL LOSS FT		
21.0	2.00	9.43	1.15	0.05	0.01	0.05	0.05	1.00	8.21	
42.0	4.00	10.26	0.23	1.25	0.35	0.05	0.26	2.00	9.43	
52.0	5.00	10.06	0.36	0.05	0.01	0.05	0.27	2.00	9.43	
65.0	6.00	11.36	1.15	0.05	0.01	0.05	0.14	5.00	10.06	
76.0	7.00	11.91	0.22	1.25	0.19	0.05	0.14	6.00	11.36	
87.0	8.00	12.20	0.00	1.25	0.15	0.05	0.14	7.00	11.91	

BEND LOSS =BEND K\* FLOWING FULL VHEAD IN SEWER.

LATERAL LOSS= OUTFLOW FULL VHEAD-JCT LOSS K\*INFLOW FULL VHEAD

FRICITION LOSS=0 MEANS IT IS NEGLIGIBLE OR POSSIBLE ERROR DUE TO JUMP.

FRICITION LOSS INCLUDES SEWER INVERT DROP AT MANHOLE

NOTICE: VHEAD DENOTES THE VELOCITY HEAD OF FULL FLOW CONDITION.

A MINIMUM JUCTION LOSS OF 0.05 FT WOULD BE INTRODUCED UNLESS LATERAL K

FRICITION LOSS WAS ESTIMATED BY BACKWATER CURVE COMPUTATIONS.

\*\*\* SUMMARY OF EARTH EXCAVATION VOLUME FOR COST ESTIMATE.

THE TRENCH SIDE SLOPE = 1

MANHOLE ID NUMBER	GROUND ELEVATION FT	INVERT ELEVATION FT	MANHOLE HEIGHT FT
1.00	11.60	6.60	5.00
2.00	17.76	7.28	10.48
4.00	16.61	7.67	8.94
5.00	19.49	8.38	11.11
6.00	17.60	9.68	7.92
7.00	16.07	10.23	5.84
8.00	15.00	10.57	4.43

SEWER ID NUMBER	UPST TRENCH WIDTH ON GROUND FT	DNST TRENCH WIDTH AT INVERT FT	UPST TRENCH WIDTH ON GROUND FT	DNST TRENCH WIDTH AT INVERT FT	TRENCH LENGTH FT	WALL THICKNESS INCHES	EARTH VOLUME CUBIC YD
21.00	19.29	5.67	8.33	5.67	136.00	4.00	370.9
42.00	17.38	4.50	20.25	4.50	57.00	3.00	210.5
52.00	20.55	5.67	19.09	5.67	200.00	4.00	865.1
65.00	14.17	5.67	20.35	5.67	240.00	4.00	847.2
76.00	10.01	5.67	13.96	5.67	89.00	4.00	182.4
87.00	7.19	5.67	9.80	5.67	47.00	4.00	64.2

TOTAL EARTH VOLUME FOR SEWER TRENCHES = 2540.243 CUBIC YARDS

SEWER FLOW LINE IS DETERMINED-BY THE USER

EARTH VOLUME WAS ESTIMATED TO HAVE

BOTTOM WIDTH=DIAMETER OR WIDTH OF SEWER + 2 \* B

B=ONE FEET WHEN DIAMETER OR WIDTH <=48 INCHES

B=TWO FEET WHEN DIAMETER OR WIDTH >48 INCHES

IF BOTTOM WIDTH <MINIMUM WIDTH, 2 FT, THE MINIMUM WIDTH WAS USED.

BACKFILL DEPTH UNDER SEWER WAS ASSUMED TO BE ONE FOOT

SEWER WALL THICKNESS=EQUIVLT DIAMATER IN INCH/12 +1 IN INCHES

CIRCULAR CHANNEL ANALYSIS  
NORMAL DEPTH COMPUTATION

December 21, 1994

PROGRAM INPUT DATA:

DESCRIPTION	VALUE
Flow Rate (cubic feet per second).....	29.9
Channel Bottom Slope (feet per foot).....	0.0063
Manning's Roughness Coefficient (n-value).....	0.0130
Channel Diameter (feet).....	3.00

PROGRAM RESULTS:

DESCRIPTION	VALUE
Normal Depth (feet).....	1.61
Flow Velocity (feet per second).....	7.72
Froude Number (Flow is Super-Critical).....	1.196
Velocity Head (feet).....	0.93
Energy Head (feet).....	2.54
Cross-Sectional Area of Flow (square feet).....	3.87
Top Width of Flow (feet).....	2.99

CIRCULAR CHANNEL ANALYSIS COMPUTER PROGRAM, Version 1.5 (c) 1986  
Dodson & Associates, Inc., 7015 W. Tidwell, #107, Houston, TX 77092  
(713) 895-8322. A complete program manual is available.

REPORT OF STORM SEWER SYSTEM DESIGN

USING UDSEWER-MODEL July-2-1993

DEVELOPED

BY

JAMES C.Y. GUO ,PHD, PE

DEPARTMENT OF CIVIL ENGINEERING, UNIVERSITY OF COLORADO AT DENVER

IN COOPERATION WITH

URBAN DRAINAGE AND FLOOD CONTROL DISTRICT

DENVER, COLORADO

\*\*\* EXECUTED BY Martin-Martin.....  
ON DATA 01-09-1995 AT TIME 09:18:21

\*\*\* PROJECT TITLE :

MAJESTIC TANDY STORM LINE A

\*\*\* RETURN PERIOD OF FLOOD IS 100 YEARS

RAINFALL INTENSITY FORMULA IS GIVEN

\*\*\* SUMMARY OF SUBBASIN RUNOFF PREDICTIONS

MANHOLE ID NUMBER	BASIN AREA * C	TIME OF CONCENTRATION			BASIN Tc (MIN)	RAIN I INCH/HR	PEAK FLOW CFS
		OVERLAND To (MIN)	GUTTER Tf (MIN)				
1.00	6.00	0.00	0.00	0.00	4.75	28.49	
2.00	6.00	0.00	0.00	0.00	4.75	28.49	
4.00	6.00	0.00	0.00	29.69	2.21	13.26	
5.00	6.00	0.00	0.00	0.00	4.75	28.49	
6.00	6.00	0.00	0.00	0.00	4.75	28.49	
7.00	6.00	0.00	0.00	0.00	4.75	28.49	
8.00	6.00	0.00	0.00	5.00	6.27	37.60	

THE SHORTEST DESIGN RAINFALL DURATION IS FIVE MINUTES

FOR RURAL AREA, BASIN TIME OF CONCENTRATION =>10 MINUTES

FOR URBAN AREA, BASIN TIME OF CONCENTRATION =>5 MINUTES

AT THE 1ST DESIGN POINT, TC <=(10+TOTAL LENGTH/180) IN MINUTES

WHEN WEIGHTED RUNOFF COEFF=> .2 , THE BASIN IS CONSIDERED TO BE URBANIZED  
WHEN TO+TF<>TC, IT INDICATES THE ABOVE DESIGN CRITERIA SUPERCEDES COMPUTATIONS

\*\*\* SUMMARY OF HYDRAULICS AT MANHOLES

MANHOLE ID NUMBER	CNTRBTING AREA * C	RAINFALL DURATION MINUTES	RAINFALL INTENSITY INCH/HR	DESIGN PEAK FLOW CFS	GROUND ELEVATION FEET	WATER ELEVATION FEET	COMMENTS
1.00	0.00	0.00	0.00	55.86	11.60	9.04	OK
2.00	0.00	29.87	0.00	55.86	17.76	9.09	OK
4.00	6.00	29.69	2.21	13.26	16.61	11.31	OK
5.00	0.00	5.89	0.00	40.10	19.49	12.20	OK
6.00	0.00	5.32	0.00	40.10	17.60	13.70	OK
7.00	0.00	5.11	0.00	40.10	16.07	15.17	OK
8.00	6.00	5.00	6.27	37.60	15.00	16.43	NO

OK MEANS WATER ELEVATION IS LOWER THAN GROUND ELEVATION

\*\*\* SUMMARY OF SEWER HYDRAULICS

NOTE: THE GIVEN FLOW DEPTH-TO-SEWER SIZE RATIO= .8

SEWER ID NUMBER	MAMHOLE UPSTREAM ID NO.	NUMBER DNSTREAM ID NO.	SEWER SHAPE	REQUIRED DIA(HIGH) (IN) (FT)	SUGGESTED DIA(HIGH) (IN) (FT)	EXISTING DIA(HIGH) (IN) (FT)	WIDTH (FT)
21.00	2.00	1.00	ROUND	39.45	42.00	36.00	0.00
42.00	4.00	2.00	ROUND	23.00	24.00	24.00	0.00
52.00	5.00	2.00	ROUND	34.84	36.00	36.00	0.00
65.00	6.00	5.00	ROUND	34.84	36.00	36.00	0.00
76.00	7.00	6.00	ROUND	34.84	36.00	36.00	0.00
87.00	8.00	7.00	ROUND	34.00	36.00	36.00	0.00

DIMENSION UNITS FOR ROUND AND ARCH SEWER ARE IN INCHES

DIMENSION UNITS FOR BOX SEWER ARE IN FEET

REQUIRED DIAMETER WAS DETERMINED BY SEWER HYDRAULIC CAPACITY.

SUGGESTED DIAMETER WAS DETERMINED BY COMMERCIALY AVAILABLE SIZE.

FOR A NEW SEWER, FLOW WAS ANALYZED BY THE SUGGESTED SEWER SIZE; OTHERWISE, EXISITNG SIZE WAS USED

SEWER ID NUMBER	DESIGN FLOW Q CFS	FLOW FULL Q CFS	NORMAL DEPTH FEET	NORAML VLCITY FPS	CRITIC DEPTH FEET	CRITIC VLCITY FPS	FULL VLCITY FPS	FROUDE NO.	COMMENT
21.0	55.9	43.9	3.00	7.90	2.42	9.15	7.90	0.00	V-OK
42.0	13.3	14.9	1.47	5.36	1.31	25.67	4.22	0.80	V-OK
52.0	40.1	43.9	2.25	7.04	2.12	2.48	5.67	0.84	V-OK
65.0	40.1	43.9	2.25	7.04	2.12	7.49	5.67	0.84	V-OK
76.0	40.1	43.9	2.25	7.04	2.12	7.49	5.67	0.84	V-OK
87.0	37.6	43.9	2.14	6.98	1.99	8.05	5.32	0.87	V-OK

FROUDE NUMBER=0 INDICATES THAT A PRESSURED FLOW OCCURS



SEWER ID NUMBER	SLOPE %	INVERT ELEVATION		BURIED DEPTH		COMMENTS
		UPSTREAM (FT)	DNSTREAM (FT)	UPSTREAM (FT)	DNSTREAM (FT)	
21.00	0.50	7.28	6.60	7.48	2.00	OK
42.00	0.50	7.67	7.39	6.94	8.38	OK
52.00	0.50	8.38	7.38	8.11	7.38	OK
65.00	0.50	9.68	8.48	4.92	8.01	OK
76.00	0.50	10.23	9.78	2.84	4.82	OK
87.00	0.50	10.57	10.34	1.43	2.73	NO

OK MEANS BURIED DEPTH IS GREATER THAN REQUIRED SOIL COVER OF 1.5 FEET

\*\*\* SUMMARY OF HYDRAULIC GRADIENT LINE ALONG SEWERS

SEWER ID NUMBER	SEWER LENGTH FEET	SURCHARGED LENGTH FEET	CROWN ELEVATION		WATER ELEVATION		FLOW CONDITION
			UPSTREAM FEET	DNSTREAM FEET	UPSTREAM FEET	DNSTREAM FEET	
21.00	136.00	0.00	10.28	9.60	9.09	9.04	PRSS'ED
42.00	57.00	57.00	9.67	9.39	11.31	9.09	PRSS'ED
52.00	200.00	30.36	11.38	10.38	12.20	9.09	SUBCR
65.00	240.00	240.00	12.68	11.48	13.70	12.20	PRSS'ED
76.00	89.00	89.00	13.23	12.78	15.17	13.70	PRSS'ED
87.00	47.00	47.00	13.57	13.34	16.43	15.17	PRSS'ED

PRSS'ED=PRESSURED FLOW; JUMP=POSSIBLE HYDRAULIC JUMP; SUBCR=SUBCRITICAL FLOW

\*\*\* SUMMARY OF ENERGY GRADIENT LINE ALONG SEWERS

SEWER ID NO	UPST MANHOLE ID NO.	SEWER ENERGY ELEV FT	FRCTION FT	BEND K COEF	JUNCTURE LOSSES			DOWNST MANHOLE ID	MANHOLE ENERGY FT
					BEND LOSS FT	LATERAL K COEF	LATERAL LOSS FT		
21.0	2.00	10.06	0.92	0.05	0.05	0.05	0.05	1.00	9.04
42.0	4.00	11.59	0.23	1.25	0.35	0.05	0.96	2.00	10.06
52.0	5.00	12.70	1.67	0.05	0.02	0.05	0.94	2.00	10.06
65.0	6.00	14.20	1.00	0.05	0.02	0.05	0.47	5.00	12.70
76.0	7.00	15.67	0.37	1.25	0.62	0.05	0.47	6.00	14.20
87.0	8.00	16.87	0.17	1.25	0.55	0.05	0.48	7.00	15.67

BEND LOSS =BEND K\* FLOWING FULL VHEAD IN SEWER.

LATERAL LOSS= OUTFLOW FULL VHEAD-JCT LOSS K\*INFLOW FULL VHEAD

FRICITION LOSS=0 MEANS IT IS NEGLIGIBLE OR POSSIBLE ERROR DUE TO JUMP.

FRICITION LOSS INCLUDES SEWER INVERT DROP AT MANHOLE

NOTICE: VHEAD DENOTES THE VELOCITY HEAD OF FULL FLOW CONDITION.

A MINIMUM JUNCTION LOSS OF 0.05 FT WOULD BE INTRODUCED UNLESS LATERAL K

FRICITION LOSS WAS ESTIMATED BY BACKWATER CURVE COMPUTATIONS.

\*\*\* SUMMARY OF EARTH EXCAVATION VOLUME FOR COST ESTIMATE.

THE TRENCH SIDE SLOPE = 1

MANHOLE ID NUMBER	GROUND ELEVATION FT	INVERT ELEVATION FT	MANHOLE HEIGHT FT
1.00	11.60	6.60	5.00
2.00	17.76	7.28	10.48
4.00	16.61	7.67	8.94
5.00	19.49	8.38	11.11
6.00	17.60	9.68	7.92
7.00	16.07	10.23	5.84
8.00	15.00	10.57	4.43

SEWER ID NUMBER	UPST TRENCH ON GROUND AT INVERT FT	WIDTH AT INVERT FT	DNST TRENCH ON GROUND AT INVERT FT	WIDTH AT INVERT FT	TRENCH LENGTH FT	WALL THICKNESS INCHES	EARTH VOLUME CUBIC YD
21.00	19.29	5.67	8.33	5.67	136.00	4.00	370.9
42.00	17.38	4.50	20.25	4.50	57.00	3.00	210.5
52.00	20.55	5.67	19.09	5.67	200.00	4.00	865.1
65.00	14.17	5.67	20.35	5.67	240.00	4.00	847.2
76.00	10.01	5.67	13.96	5.67	89.00	4.00	182.4
87.00	7.19	5.67	9.80	5.67	47.00	4.00	64.2

TOTAL EARTH VOLUME FOR SEWER TRENCHES = 2540.243 CUBIC YARDS  
SEWER FLOW LINE IS DETERMINED BY THE USER

EARTH VOLUME WAS ESTIMATED TO HAVE

BOTTOM WIDTH=DIAMETER OR WIDTH OF SEWER + 2 \* B

B=ONE FEET WHEN DIAMETER OR WIDTH <=48 INCHES

B=TWO FEET WHEN DIAMETER OR WIDTH >48 INCHES

IF BOTTOM WIDTH <MINIMUM WIDTH, 2 FT, THE MINIMUM WIDTH WAS USED.

BACKFILL DEPTH UNDER SEWER WAS ASSUMED TO BE ONE FOOT

SEWER WALL THICKNESS=EQVILNT DIAMATER IN INCH/12 +1 IN INCHES

CIRCULAR CHANNEL ANALYSIS  
NORMAL DEPTH COMPUTATION

December 21, 1994

PROGRAM INPUT DATA:

DESCRIPTION	VALUE
Flow Rate (cubic feet per second).....	55.6
Channel Bottom Slope (feet per foot).....	0.0063
Manning's Roughness Coefficient (n-value).....	0.0130
Channel Diameter (feet).....	3.00

PROGRAM RESULTS:

DESCRIPTION	VALUE
Normal Depth (feet).....	2.44
Flow Velocity (feet per second).....	9.04
Froude Number (Flow is Sub-Critical).....	0.983
Velocity Head (feet).....	1.27
Energy Head (feet).....	3.71
Cross-Sectional Area of Flow (square feet).....	6.15
Top Width of Flow (feet).....	2.34

CIRCULAR CHANNEL ANALYSIS COMPUTER PROGRAM, Version 1.5 (c) 1986  
Dodson & Associates, Inc., 7015 W. Tidwell, #107, Houston, TX 77092  
(713) 895-8322. A complete program manual is available.

=====

REPORT OF STORM SEWER SYSTEM DESIGN

USING UDSEWER-MODEL July-2-1993

DEVELOPED

BY

JAMES C.Y. GUO ,PHD, PE

DEPARTMENT OF CIVIL ENGINEERING, UNIVERSITY OF COLORADO AT DENVER

IN COOPERATION WITH

URBAN DRAINAGE AND FLOOD CONTROL DISTRICT

DENVER, COLORADO

=====

\*\*\* EXECUTED BY Martin-Martin.....  
 ON DATA 12-21-1994 AT TIME 09:57:20

\*\*\* PROJECT TITLE :

MAJESTIC TANDY STORM LINE B

\*\*\* RETURN PERIOD OF FLOOD IS 5 YEARS

RAINFALL INTENSITY FORMULA IS GIVEN

\*\*\* SUMMARY OF SUBBASIN RUNOFF PREDICTIONS

MANHOLE ID NUMBER	BASIN AREA * C	TIME OF CONCENTRATION			BASIN Tc (MIN)	RAIN I INCH/HR	PEAK FLOW CFS
		OVERLAND To (MIN)	GUTTER Tf (MIN)				
1.00	6.00	0.00	0.00	0.00	4.75	28.49	
2.00	6.00	0.00	0.00	0.00	4.75	28.49	
3.00	6.00	0.00	0.00	0.00	4.75	28.49	
4.00	6.00	0.00	0.00	330.21	0.41	2.45	
5.00	6.00	0.00	0.00	0.00	4.75	28.49	
6.00	6.00	0.00	0.00	330.21	0.41	2.45	
7.00	6.00	0.00	0.00	0.00	4.75	28.49	
8.00	6.00	0.00	0.00	0.00	4.75	28.49	
9.00	6.00	0.00	0.00	0.00	4.75	28.49	
10.00	6.00	0.00	0.00	297.89	0.44	2.65	
11.00	6.00	0.00	0.00	0.00	4.75	28.49	
12.00	6.00	0.00	0.00	0.00	4.75	28.49	
13.00	6.00	0.00	0.00	0.00	4.75	28.49	
14.00	6.00	0.00	0.00	0.00	4.75	28.49	
15.00	6.00	0.00	0.00	479.73	0.31	1.84	
16.00	6.00	0.00	0.00	479.73	0.31	1.84	

17.00      6.00      0.00      0.00      539.82      0.28      1.68

THE SHORTEST DESIGN RAINFALL DURATION IS FIVE MINUTES

FOR RURAL AREA, BASIN TIME OF CONCENTRATION =>10 MINUTES

FOR URBAN AREA, BASIN TIME OF CONCENTRATION =>5 MINUTES

AT THE 1ST DESIGN POINT, TC <=(10+TOTAL LENGTH/180) IN MINUTES

WHEN WEIGHTED RUNOFF COEFF=> .2 , THE BASIN IS CONSIDERED TO BE URBANIZED

WHEN TO+TF<>TC, IT INDICATES THE ABOVE DESIGN CRITERIA SUPERCEDES COMPUTATIONS

\*\*\* SUMMARY OF HYDRAULICS AT MANHOLES

MANHOLE ID NUMBER	CNTRBTING AREA * C	RAINFALL DURATION MINUTES	RAINFALL INTENSITY INCH/HR	DESIGN PEAK FLOW CFS	GROUND ELEVATION FEET	WATER ELEVATION FEET	COMMENTS
1.00	0.00	0.00	0.00	26.10	13.40	9.95	OK
2.00	0.00	544.03	0.00	49.23	17.30	11.23	OK
3.00	0.00	330.65	0.00	7.35	21.50	15.86	OK
4.00	6.00	330.21	0.41	2.45	21.35	18.61	OK
5.00	0.00	330.34	0.00	4.90	24.67	18.07	OK
6.00	6.00	330.21	0.41	2.45	24.65	18.89	OK
7.00	0.00	543.43	0.00	18.75	16.20	12.78	OK
8.00	0.00	542.87	0.00	13.85	18.69	13.11	OK
9.00	0.00	542.15	0.00	13.85	22.63	14.21	OK
10.00	6.00	297.89	0.44	2.65	16.95	14.29	OK
11.00	0.00	541.85	0.00	11.20	19.00	14.90	OK
12.00	0.00	541.43	0.00	11.20	22.36	15.06	OK
13.00	0.00	541.12	0.00	7.52	22.67	16.18	OK
14.00	0.00	540.82	0.00	5.36	23.54	16.54	OK
15.00	6.00	479.73	0.31	1.84	26.00	16.82	OK
16.00	6.00	479.73	0.31	1.84	26.00	16.67	OK
17.00	6.00	539.82	0.28	1.68	23.29	17.95	OK

OK MEANS WATER ELEVATION IS LOWER THAN GROUND ELEVATION

\*\*\* SUMMARY OF SEWER HYDRAULICS

NOTE: THE GIVEN FLOW DEPTH-TO-SEWER SIZE RATIO= .8

SEWER ID NUMBER	MAMHOLE UPSTREAM ID NO.	NUMBER DNSTREAM ID NO.	SEWER SHAPE	REQUIRED DIA(HIGH) (IN) (FT)	SUGGESTED DIA(HIGH) (IN) (FT)	EXISTING DIA(HIGH) (IN) (FT)	WIDTH (FT)
21.00	2.00	1.00	ROUND	37.62	42.00	36.00	0.00
32.00	3.00	2.00	ROUND	12.06	18.00	18.00	0.00
43.00	4.00	3.00	ROUND	9.45	18.00	18.00	0.00
53.00	5.00	3.00	ROUND	12.21	18.00	18.00	0.00
65.00	6.00	5.00	ROUND	9.42	18.00	18.00	0.00
72.00	7.00	2.00	ROUND	26.19	27.00	36.00	0.00
87.00	8.00	7.00	ROUND	22.26	24.00	30.00	0.00
98.00	9.00	8.00	ROUND	23.38	24.00	30.00	0.00
109.00	10.00	9.00	ROUND	12.58	18.00	24.00	0.00

119.00	11.00	9.00	ROUND	21.59	24.00	24.00	0.00
1211.00	12.00	11.00	ROUND	21.59	24.00	24.00	0.00
1312.00	13.00	12.00	ROUND	18.60	21.00	24.00	0.00
1413.00	14.00	13.00	ROUND	16.38	18.00	24.00	0.00
1514.00	15.00	14.00	ROUND	10.97	18.00	15.00	0.00
1614.00	16.00	14.00	ROUND	10.97	18.00	18.00	0.00
1714.00	17.00	14.00	ROUND	9.78	18.00	24.00	0.00

DIMENSION UNITS FOR ROUND AND ARCH SEWER ARE IN INCHES  
 DIMENSION UNITS FOR BOX SEWER ARE IN FEET  
 REQUIRED DIAMETER WAS DETERMINED BY SEWER HYDRAULIC CAPACITY.  
 SUGGESTED DIAMETER WAS DETERMINED BY COMMERCIALY AVAILABLE SIZE.  
 FOR A NEW SEWER, FLOW WAS ANALYZED BY THE SUGGESTED SEWER SIZE; OTHERWISE,  
 EXISTING SIZE WAS USED

SEWER ID NUMBER	DESIGN FLOW Q CFS	FLOW FULL Q CFS	NORMAL DEPTH FEET	NORAML VLCITY FPS	CRITIC DEPTH FEET	CRITIC VLCITY FPS	FULL VLCITY FPS	FROUDE NO.	COMMENT
21.0	49.2	43.9	3.00	6.96	2.29	4.52	6.96	0.00	V-OK
32.0	7.3	21.4	0.61	10.99	1.06	36.80	4.16	2.87	V-OK
43.0	2.5	13.7	0.43	5.86	0.61	10.86	1.39	1.86	V-OK
53.0	4.9	13.8	0.62	7.15	0.85	2.37	2.77	1.85	V-OK
65.0	2.5	13.8	0.43	5.90	0.61	7.24	1.39	1.88	V-OK
72.0	18.8	43.9	1.37	5.97	1.39	0.76	2.65	1.03	V-OK
87.0	13.9	30.8	1.18	6.10	1.28	7.43	2.82	1.13	V-OK
98.0	13.9	27.0	1.27	5.54	1.28	5.49	2.82	0.98	V-OK
109.0	2.7	14.9	0.57	3.58	0.59	17.71	0.84	0.99	V-OK
119.0	11.2	14.9	1.29	5.21	1.20	1.35	3.57	0.87	V-OK
1211.0	11.2	14.9	1.29	5.21	1.20	5.71	3.57	0.87	V-OK
1312.0	7.5	14.9	1.01	4.75	1.00	7.11	2.39	0.94	V-OK
1413.0	5.4	14.9	0.83	4.35	0.84	6.05	1.71	0.97	V-OK
1514.0	1.8	4.3	0.57	3.34	0.55	10.41	1.50	0.89	V-OK
1614.0	1.8	6.9	0.53	3.31	0.53	3.32	1.04	0.94	V-OK
1714.0	1.7	18.5	0.41	3.66	0.49	3.06	0.53	1.21	V-OK

FROUDE NUMBER=0 INDICATES THAT A PRESSURED FLOW OCCURS

SEWER ID NUMBER	SLOPE %	INVERT UPSTREAM (FT)	ELEVATION DNSTREAM (FT)	BURIED UPSTREAM (FT)	DEPTH DNSTREAM (FT)	COMMENTS
21.00	0.50	8.60	8.40	5.70	2.00	OK
32.00	4.80	14.80	8.80	5.20	7.00	OK
43.00	1.96	18.00	15.02	1.85	4.98	OK
53.00	2.00	17.22	15.00	5.95	5.00	OK
65.00	2.00	18.28	17.42	4.87	5.75	OK
72.00	0.50	9.88	8.81	3.32	5.49	OK
87.00	0.65	11.42	10.09	4.77	3.61	OK
98.00	0.50	12.82	11.62	7.31	4.57	OK
109.00	0.50	13.45	12.99	1.50	7.63	OK
119.00	0.50	13.48	13.02	3.52	7.61	OK
1211.00	0.50	14.34	13.68	6.02	3.32	OK
1312.00	0.50	14.98	14.54	5.69	5.82	OK
1413.00	0.50	15.57	15.18	5.97	5.49	OK

1514.00	0.50	16.20	15.77	8.55	6.52	OK
1614.00	0.50	16.10	15.77	8.40	6.27	OK
1714.00	0.77	17.46	15.77	3.83	5.77	OK

OK MEANS BURIED DEPTH IS GREATER THAN REQUIRED SOIL COVER OF 1.5 FEET

\*\*\* SUMMARY OF HYDRAULIC GRADIENT LINE ALONG SEWERS

SEWER ID NUMBER	SEWER SURCHARGED LENGTH FEET	SEWER SURCHARGED LENGTH FEET	CROWN ELEVATION		WATER ELEVATION		FLOW CONDITION
			UPSTREAM FEET	DNSTREAM FEET	UPSTREAM FEET	DNSTREAM FEET	
21.00	40.00	0.00	11.60	11.40	11.23	9.95	PRSS'ED
32.00	125.00	45.17	16.30	10.30	15.86	11.23	JUMP
43.00	152.00	0.00	19.50	16.52	18.61	15.86	JUMP
53.00	111.00	0.00	18.72	16.50	18.07	15.86	JUMP
65.00	43.00	0.00	19.78	18.92	18.89	18.07	JUMP
72.00	215.00	164.53	12.88	11.81	12.78	11.23	JUMP
87.00	205.00	66.66	13.92	12.59	13.11	12.78	JUMP
98.00	240.00	0.00	15.32	14.12	14.21	13.11	SUBCR
109.00	91.00	0.00	15.45	14.99	14.29	14.21	SUBCR
119.00	92.00	0.00	15.48	15.02	14.90	14.21	SUBCR
1211.00	133.00	0.00	16.34	15.68	15.06	14.90	SUBCR
1312.00	87.00	0.00	16.98	16.54	16.18	15.06	SUBCR
1413.00	78.00	0.00	17.57	17.18	16.54	16.18	SUBCR
1514.00	86.00	0.00	17.45	17.02	16.82	16.54	SUBCR
1614.00	66.00	0.00	17.60	17.27	16.67	16.54	SUBCR
1714.00	220.00	0.00	19.46	17.77	17.95	16.54	JUMP

PRSS'ED=PRESSURED FLOW; JUMP=POSSIBLE HYDRAULIC JUMP; SUBCR=SUBCRITICAL FLOW

\*\*\* SUMMARY OF ENERGY GRADIENT LINE ALONG SEWERS

SEWER ID NO	UPST MANHOLE ID NO.	SEWER ENERGY ELEV FT	SEWER FRCTION FT	BEND K COEF	JUNCTURE LOSSES			DOWNST MANHOLE ID	SEWER ENERGY FT
					BEND LOSS FT	LATERAL LATERAL LOSS FT	LATERAL LATERAL LOSS FT		
21.0	2.00	11.98	1.95	0.05	0.04	0.05	0.05	1.00	9.95
32.0	3.00	16.13	3.39	0.05	0.01	0.05	0.74	2.00	11.98
43.0	4.00	18.64	2.21	1.25	0.04	0.05	0.27	3.00	16.13
53.0	5.00	18.19	1.65	1.25	0.15	0.05	0.26	3.00	16.13
65.0	6.00	18.92	0.58	1.25	0.04	0.05	0.12	5.00	18.19
72.0	7.00	12.89	0.15	0.05	0.01	0.05	0.75	2.00	11.98
87.0	8.00	13.23	0.09	1.25	0.15	0.05	0.10	7.00	12.89
98.0	9.00	14.34	0.98	0.05	0.01	0.05	0.12	8.00	13.23
109.0	10.00	14.30	0.00	0.05	0.00	0.05	0.12	9.00	14.34
119.0	11.00	15.10	0.64	0.05	0.01	0.05	0.11	9.00	14.34
1211.0	12.00	15.26	0.00	0.05	0.01	0.05	0.19	11.00	15.10
1312.0	13.00	16.27	0.82	0.05	0.00	0.05	0.19	12.00	15.26
1413.0	14.00	16.59	0.18	1.25	0.06	0.05	0.09	13.00	16.27

1514.0	15.00	16.85	0.22	0.05	0.00	0.05	0.04	14.00	16.59
1614.0	16.00	16.69	0.06	0.05	0.00	0.05	0.04	14.00	16.59
1714.0	17.00	17.96	1.32	1.25	0.01	0.05	0.04	14.00	16.59

BEND LOSS = BEND K \* FLOWING FULL VHEAD IN SEWER.

LATERAL LOSS = OUTFLOW FULL VHEAD - JCT LOSS K \* INFLOW FULL VHEAD

FRICTION LOSS = 0 MEANS IT IS NEGLIGIBLE OR POSSIBLE ERROR DUE TO JUMP.

FRICTION LOSS INCLUDES SEWER INVERT DROP AT MANHOLE

NOTICE: VHEAD DENOTES THE VELOCITY HEAD OF FULL FLOW CONDITION.

A MINIMUM JUNCTION LOSS OF 0.05 FT WOULD BE INTRODUCED UNLESS LATERAL K FRICTION LOSS WAS ESTIMATED BY BACKWATER CURVE COMPUTATIONS.

\*\*\* SUMMARY OF EARTH EXCAVATION VOLUME FOR COST ESTIMATE.

THE TRENCH SIDE SLOPE = 1

MANHOLE ID NUMBER	GROUND ELEVATION FT	INVERT ELEVATION FT	MANHOLE HEIGHT FT
1.00	13.40	8.40	5.00
2.00	17.30	8.60	8.70
3.00	21.50	14.80	6.70
4.00	21.35	18.00	3.35
5.00	24.67	17.22	7.45
6.00	24.65	18.28	6.37
7.00	16.20	9.88	6.32
8.00	18.69	11.42	7.27
9.00	22.63	12.82	9.81
10.00	16.95	13.45	3.50
11.00	19.00	13.48	5.52
12.00	22.36	14.34	8.02
13.00	22.67	14.98	7.69
14.00	23.54	15.57	7.97
15.00	26.00	16.20	9.80
16.00	26.00	16.10	9.90
17.00	23.29	17.46	5.83

SEWER ID NUMBER	UPST TRENCH ON GROUND AT FT	TRENCH WIDTH AT INVERT FT	DNST TRENCH ON GROUND AT INVERT FT	TRENCH WIDTH AT INVERT FT	TRENCH LENGTH FT	WALL THICKNESS INCHES	EARTH VOLUME CUBIC YD
21.00	15.73	5.67	8.33	5.67	40.00	4.00	86.0
32.00	13.48	3.92	17.08	3.92	125.00	2.50	309.2
43.00	6.78	3.92	13.04	3.92	152.00	2.50	194.8
53.00	14.98	3.92	13.08	3.92	111.00	2.50	234.5
65.00	12.82	3.92	14.58	3.92	43.00	2.50	87.2
72.00	10.97	5.67	15.32	5.67	215.00	4.00	500.2
87.00	13.46	5.08	11.14	5.08	205.00	3.50	398.2
98.00	18.54	5.08	13.06	5.08	240.00	3.50	698.3
109.00	6.50	4.50	18.77	4.50	91.00	3.00	202.2
119.00	10.54	4.50	18.72	4.50	92.00	3.00	233.0
1211.00	15.54	4.50	10.15	4.50	133.00	3.00	264.8
1312.00	14.88	4.50	15.13	4.50	87.00	3.00	215.8
1413.00	15.44	4.50	14.48	4.50	78.00	3.00	192.7



1514.00	19.97	3.63	15.92	3.63	86.00	2.25	279.6
1614.00	19.88	3.92	15.62	3.92	66.00	2.50	213.9
1714.00	11.16	4.50	15.05	4.50	220.00	3.00	444.6

\_TOTAL EARTH VOLUME FOR SEWER TRENCHES = 4555.006 CUBIC YARDS  
 SEWER FLOW LINE IS DETERMINED BY THE USER

EARTH VOLUME WAS ESTIMATED TO HAVE

BOTTOM WIDTH=DIAMETER OR WIDTH OF SEWER + 2 \* B

B=ONE FEET WHEN DIAMETER OR WIDTH <=48 INCHES

B=TWO FEET WHEN DIAMETER OR WIDTH >48 INCHES

IF BOTTOM WIDTH <MINIMUM WIDTH, 2 FT, THE MINIMUM WIDTH WAS USED.

BACKFILL DEPTH UNDER SEWER WAS ASSUMED TO BE ONE FOOT

SEWER WALL THICKNESS=EQUIVLENT DIAMETER IN INCH/12 +1 IN INCHES

CIRCULAR CHANNEL ANALYSIS  
NORMAL DEPTH COMPUTATION

December 21, 1994

PROGRAM INPUT DATA:

DESCRIPTION	VALUE
Flow Rate (cubic feet per second).....	26.1
Channel Bottom Slope (feet per foot).....	0.0050
Manning's Roughness Coefficient (n-value).....	0.0130
Channel Diameter (feet).....	3.00

PROGRAM RESULTS:

DESCRIPTION	VALUE
Normal Depth (feet).....	1.55
Flow Velocity (feet per second).....	7.10
Froude Number (Flow is Super-Critical).....	1.131
Velocity Head (feet).....	0.78
Energy Head (feet).....	2.33
Cross-Sectional Area of Flow (square feet).....	3.67
Top Width of Flow (feet).....	3.00

CIRCULAR CHANNEL ANALYSIS COMPUTER PROGRAM, Version 1.5 (c) 1986  
Dodson & Associates, Inc., 7015 W. Tidwell, #107, Houston, TX 77092  
(713) 895-8322. A complete program manual is available.

=====

REPORT OF STORM SEWER SYSTEM DESIGN

USING UDSEWER-MODEL July-2-1993

DEVELOPED

BY

JAMES C.Y. GUO ,PHD, PE

DEPARTMENT OF CIVIL ENGINEERING, UNIVERSITY OF COLORADO AT DENVER

IN COOPERATION WITH

URBAN DRAINAGE AND FLOOD CONTROL DISTRICT

DENVER, COLORADO

=====

\*\*\* EXECUTED BY Martin-Martin.....  
ON DATA 12-21-1994 AT TIME 09:41:32

\*\*\* PROJECT TITLE :

MAJESTIC TANDY STORM LINE B

\*\*\* RETURN PERIOD OF FLOOD IS 100 YEARS

RAINFALL INTENSITY FORMULA IS GIVEN

\*\*\* SUMMARY OF SUBBASIN RUNOFF PREDICTIONS

MANHOLE ID NUMBER	BASIN AREA * C	TIME OF CONCENTRATION			BASIN Tc (MIN)	RAIN I INCH/HR	PEAK FLOW CFS
		OVERLAND To (MIN)	GUTTER Tf (MIN)				
1.00	6.00	0.00	0.00	0.00	4.75	28.49	
2.00	6.00	0.00	0.00	0.00	4.75	28.49	
3.00	6.00	0.00	0.00	0.00	4.75	28.49	
4.00	6.00	0.00	0.00	136.93	0.79	4.74	
5.00	6.00	0.00	0.00	0.00	4.75	28.49	
6.00	6.00	0.00	0.00	136.93	0.79	4.74	
7.00	6.00	0.00	0.00	0.00	4.75	28.49	
8.00	6.00	0.00	0.00	0.00	4.75	28.49	
9.00	6.00	0.00	0.00	0.00	4.75	28.49	
10.00	6.00	0.00	0.00	109.39	0.93	5.58	
11.00	6.00	0.00	0.00	0.00	4.75	28.49	
12.00	6.00	0.00	0.00	0.00	4.75	28.49	
13.00	6.00	0.00	0.00	0.00	4.75	28.49	
14.00	6.00	0.00	0.00	0.00	4.75	28.49	
15.00	6.00	0.00	0.00	201.49	0.59	3.56	
16.00	6.00	0.00	0.00	202.25	0.59	3.55	

17.00      6.00      0.00      0.00      371.30      0.37      2.24

THE SHORTEST DESIGN RAINFALL DURATION IS FIVE MINUTES

FOR RURAL AREA, BASIN TIME OF CONCENTRATION =>10 MINUTES

FOR URBAN AREA, BASIN TIME OF CONCENTRATION =>5 MINUTES

AT THE 1ST DESIGN POINT, TC <=(10+TOTAL LENGTH/180) IN MINUTES

WHEN WEIGHTED RUNOFF COEFF=> .2 , THE BASIN IS CONSIDERED TO BE URBANIZED

WHEN TO+TF<>TC, IT INDICATES THE ABOVE DESIGN CRITERIA SUPERCEDES COMPUTATIONS

\*\*\* SUMMARY OF HYDRAULICS AT MANHOLES

MANHOLE ID NUMBER	CNTRBTNG AREA * C	RAINFALL DURATION MINUTES	RAINFALL INTENSITY INCH/HR	DESIGN PEAK FLOW CFS	GROUND ELEVATION FEET	WATER ELEVATION FEET	COMMENTS
1.00	0.00	0.00	0.00	49.23	13.40	11.00	OK
2.00	0.00	375.02	0.00	49.23	17.30	11.15	OK
3.00	0.00	137.29	0.00	14.22	21.50	16.16	OK
4.00	6.00	136.93	0.79	4.74	21.35	18.84	OK
5.00	0.00	137.03	0.00	9.48	24.67	19.09	OK
6.00	6.00	136.93	0.79	4.74	24.65	20.11	OK
7.00	0.00	374.50	0.00	35.01	16.20	13.58	OK
8.00	0.00	374.01	0.00	24.93	18.69	15.30	OK
9.00	0.00	373.37	0.00	24.93	22.63	16.72	OK
10.00	6.00	109.39	0.93	5.58	16.95	17.45	NO
11.00	0.00	373.12	0.00	19.35	19.00	17.71	OK
12.00	0.00	372.76	0.00	19.35	22.36	19.42	OK
13.00	0.00	372.48	0.00	16.46	22.67	20.70	OK
14.00	0.00	372.22	0.00	9.35	23.54	21.74	OK
15.00	6.00	201.49	0.59	3.56	26.00	22.18	OK
16.00	6.00	202.25	0.59	3.55	26.00	22.04	OK
17.00	6.00	371.30	0.37	2.24	23.29	22.04	OK

OK MEANS WATER ELEVATION IS LOWER THAN GROUND ELEVATION

\*\*\* SUMMARY OF SEWER HYDRAULICS

NOTE: THE GIVEN FLOW DEPTH-TO-SEWER SIZE RATIO= .8

SEWER ID NUMBER	MAMHOLE UPSTREAM ID NO.	NUMBER DNSTREAM ID NO.	SEWER SHAPE	REQUIRED DIA(HIGH) (IN)	SUGGESTED DIA(HIGH) (FT)	EXISTING DIA(HIGH) (IN)	EXISTING WIDTH (FT)
21.00	2.00	1.00	ROUND	37.62	42.00	36.00	0.00
32.00	3.00	2.00	ROUND	15.45	18.00	18.00	0.00
43.00	4.00	3.00	ROUND	12.11	18.00	18.00	0.00
53.00	5.00	3.00	ROUND	15.64	18.00	18.00	0.00
65.00	6.00	5.00	ROUND	12.06	18.00	18.00	0.00
72.00	7.00	2.00	ROUND	33.11	36.00	36.00	0.00
87.00	8.00	7.00	ROUND	27.75	30.00	30.00	0.00
98.00	9.00	8.00	ROUND	29.15	30.00	30.00	0.00
109.00	10.00	9.00	ROUND	16.63	18.00	24.00	0.00

119.00	11.00	9.00	ROUND	26.51	27.00	24.00	0.00
1211.00	12.00	11.00	ROUND	26.51	27.00	24.00	0.00
1312.00	13.00	12.00	ROUND	24.95	27.00	24.00	0.00
1413.00	14.00	13.00	ROUND	20.18	21.00	24.00	0.00
1514.00	15.00	14.00	ROUND	14.05	18.00	15.00	0.00
1614.00	16.00	14.00	ROUND	14.03	18.00	18.00	0.00
1714.00	17.00	14.00	ROUND	10.89	18.00	24.00	0.00

DIMENSION UNITS FOR ROUND AND ARCH SEWER ARE IN INCHES

DIMENSION UNITS FOR BOX SEWER ARE IN FEET

REQUIRED DIAMETER WAS DETERMINED BY SEWER HYDRAULIC CAPACITY.

SUGGESTED DIAMETER WAS DETERMINED BY COMMERCIALY AVAILABLE SIZE.

FOR A NEW SEWER, FLOW WAS ANALYZED BY THE SUGGESTED SEWER SIZE; OTHERWISE, EXISITNG SIZE WAS USED

SEWER ID NUMBER	DESIGN FLOW Q CFS	FLOW FULL Q CFS	NORMAL DEPTH FEET	NORAML VLCITY FPS	CRITIC DEPTH FEET	CRITIC VLCITY FPS	FULL VLCITY FPS	FROUDE NO.	COMMENT
21.0	49.2	43.9	3.00	6.96	2.29	8.52	6.96	0.00	V-OK
32.0	14.2	21.4	0.89	12.97	1.36	29.16	8.05	2.65	V-OK
43.0	4.7	13.7	0.61	7.04	0.84	14.01	2.68	1.84	V-OK
53.0	9.5	13.8	0.91	8.43	1.19	3.16	5.36	1.70	V-OK
65.0	4.7	13.8	0.61	7.09	0.84	9.34	2.68	1.85	V-OK
72.0	35.0	43.9	2.02	6.90	1.92	0.99	4.95	0.90	V-OK
87.0	24.9	30.8	1.71	6.98	1.70	9.86	5.08	0.99	V-OK
98.0	24.9	27.0	1.90	6.24	1.70	7.02	5.08	0.81	V-OK
109.0	5.6	14.9	0.85	4.40	0.85	19.63	1.78	0.97	V-OK
119.0	19.4	14.9	2.00	6.16	1.58	2.10	6.16	0.00	V-OK
1211.0	19.4	14.9	2.00	6.16	1.58	7.27	6.16	0.00	V-OK
1312.0	16.5	14.9	2.00	5.24	1.46	7.86	5.24	0.00	V-OK
1413.0	9.4	14.9	1.15	5.01	1.10	9.33	2.98	0.91	V-OK
1514.0	3.6	4.3	0.87	3.88	0.76	11.99	2.90	0.76	V-OK
1614.0	3.6	6.9	0.76	3.94	0.74	4.08	2.01	0.90	V-OK
1714.0	2.2	18.5	0.47	3.98	0.56	4.90	0.71	1.22	V-OK

FROUDE NUMBER=0 INDICATES THAT A PRESSURED FLOW OCCURS

SEWER ID NUMBER	SLOPE %	INVERT ELEVATION		BURIED DEPTH		COMMENTS
		UPSTREAM (FT)	DNSTREAM (FT)	UPSTREAM (FT)	DNSTREAM (FT)	
21.00	0.50	8.60	8.40	5.70	2.00	OK
32.00	4.80	14.80	8.80	5.20	7.00	OK
43.00	1.96	18.00	15.02	1.85	4.98	OK
53.00	2.00	17.22	15.00	5.95	5.00	OK
65.00	2.00	18.28	17.42	4.87	5.75	OK
72.00	0.50	9.88	8.81	3.32	5.49	OK
87.00	0.65	11.42	10.09	4.77	3.61	OK
98.00	0.50	12.82	11.62	7.31	4.57	OK
109.00	0.50	13.45	12.99	1.50	7.63	OK
119.00	0.50	13.48	13.02	3.52	7.61	OK
1211.00	0.50	14.34	13.68	6.02	3.32	OK
1312.00	0.50	14.98	14.54	5.69	5.82	OK
1413.00	0.50	15.57	15.18	5.97	5.49	OK

1514.00	0.50	16.20	15.77	8.55	6.52	OK
1614.00	0.50	16.10	15.77	8.40	6.27	OK
1714.00	0.77	17.46	15.77	3.83	5.77	OK

OK MEANS BURIED DEPTH IS GREATER THAN REQUIRED SOIL COVER OF 1.5 FEET

\*\*\* SUMMARY OF HYDRAULIC GRADIENT LINE ALONG SEWERS

SEWER ID NUMBER	SEWER LENGTH FEET	SURCHARGED LENGTH FEET	CROWN ELEVATION UPSTREAM FEET	CROWN ELEVATION DNSTREAM FEET	WATER ELEVATION UPSTREAM FEET	WATER ELEVATION DNSTREAM FEET	FLOW CONDITION
21.00	40.00	0.00	11.60	11.40	11.15	11.00	PRSS'ED
32.00	125.00	28.15	16.30	10.30	16.16	11.15	JUMP
43.00	152.00	85.59	19.50	16.52	18.84	16.16	JUMP
53.00	111.00	88.26	18.72	16.50	19.09	16.16	JUMP
65.00	43.00	43.00	19.78	18.92	20.11	19.09	PRSS'ED
72.00	215.00	94.11	12.88	11.81	13.58	11.15	SUBCR
87.00	205.00	205.00	13.92	12.59	15.30	13.58	PRSS'ED
98.00	240.00	240.00	15.32	14.12	16.72	15.30	PRSS'ED
109.00	91.00	91.00	15.45	14.99	17.54	16.72	PRSS'ED
119.00	92.00	92.00	15.48	15.02	17.71	16.72	PRSS'ED
1211.00	133.00	133.00	16.34	15.68	19.42	17.71	PRSS'ED
1312.00	87.00	87.00	16.98	16.54	20.70	19.42	PRSS'ED
1413.00	78.00	78.00	17.57	17.18	21.74	20.70	PRSS'ED
1514.00	86.00	86.00	17.45	17.02	22.18	21.74	PRSS'ED
1614.00	66.00	66.00	17.60	17.27	22.04	21.74	PRSS'ED
1714.00	220.00	220.00	19.46	17.77	22.04	21.74	PRSS'ED

PRSS'ED=PRESSURED FLOW; JUMP=POSSIBLE HYDRAULIC JUMP; SUBCR=SUBCRITICAL FLOW

\*\*\* SUMMARY OF ENERGY GRADIENT LINE ALONG SEWERS

SEWER ID NO	UPST MANHOLE ID NO.	SEWER ENERGY ELEV FT	SEWER FRCION FT	BEND K COEF	JUNCTURE LOSSES BEND LOSS FT	LATERAL LATERAL LOSS FT	DOWNST MANHOLE ID	SEWER ENERGY FT
21.0	2.00	11.90	0.82	0.05	0.04	0.05	1.00	11.00
32.0	3.00	17.17	4.51	0.05	0.05	0.05	2.00	11.90
43.0	4.00	18.95	0.64	1.25	0.14	0.05	3.00	17.17
53.0	5.00	19.54	0.83	1.25	0.56	0.05	3.00	17.17
65.0	6.00	20.22	0.10	1.25	0.14	0.05	5.00	19.54
72.0	7.00	13.97	1.31	0.05	0.02	0.05	2.00	11.90
87.0	8.00	15.70	0.87	1.25	0.50	0.05	7.00	13.97
98.0	9.00	17.12	1.02	0.05	0.02	0.05	8.00	15.70
109.0	10.00	17.59	0.06	0.05	0.00	0.05	9.00	17.12
119.0	11.00	18.30	0.78	0.05	0.03	0.05	9.00	17.12
1211.0	12.00	20.01	1.12	0.05	0.03	0.05	11.00	18.30
1312.0	13.00	21.13	0.53	0.05	0.02	0.05	12.00	20.01
1413.0	14.00	21.88	0.15	1.25	0.17	0.05	13.00	21.13

1514.0	15.00	22.31	0.30	0.05	0.01	0.05	0.13	14.00	21.88
1614.0	16.00	22.10	0.09	0.05	0.00	0.05	0.13	14.00	21.88
1714.0	17.00	22.05	0.02	1.25	0.01	0.05	0.14	14.00	21.88

BEND LOSS = BEND K \* FLOWING FULL VHEAD IN SEWER.

LATERAL LOSS = OUTFLOW FULL VHEAD - JCT LOSS K \* INFLOW FULL VHEAD

FRICITION LOSS = 0 MEANS IT IS NEGLIGIBLE OR POSSIBLE ERROR DUE TO JUMP.

FRICITION LOSS INCLUDES SEWER INVERT DROP AT MANHOLE

NOTICE: VHEAD DENOTES THE VELOCITY HEAD OF FULL FLOW CONDITION.

A MINIMUM JUNCTION LOSS OF 0.05 FT WOULD BE INTRODUCED UNLESS LATERAL K FRICITION LOSS WAS ESTIMATED BY BACKWATER CURVE COMPUTATIONS.

\*\*\* SUMMARY OF EARTH EXCAVATION VOLUME FOR COST ESTIMATE.

THE TRENCH SIDE SLOPE = 1

MANHOLE ID NUMBER	GROUND ELEVATION FT	INVERT ELEVATION FT	MANHOLE HEIGHT FT
1.00	13.40	8.40	5.00
2.00	17.30	8.60	8.70
3.00	21.50	14.80	6.70
4.00	21.35	18.00	3.35
5.00	24.67	17.22	7.45
6.00	24.65	18.28	6.37
7.00	16.20	9.88	6.32
8.00	18.69	11.42	7.27
9.00	22.63	12.82	9.81
10.00	16.95	13.45	3.50
11.00	19.00	13.48	5.52
12.00	22.36	14.34	8.02
13.00	22.67	14.98	7.69
14.00	23.54	15.57	7.97
15.00	26.00	16.20	9.80
16.00	26.00	16.10	9.90
17.00	23.29	17.46	5.83

SEWER ID NUMBER	UPST TRENCH WIDTH ON GROUND FT	TRENCH WIDTH AT INVERT FT	DNST TRENCH WIDTH ON GROUND FT	TRENCH WIDTH AT INVERT FT	TRENCH LENGTH FT	WALL THICKNESS INCHES	EARTH VOLUME CUBIC YD
21.00	15.73	5.67	8.33	5.67	40.00	4.00	86.0
32.00	13.48	3.92	17.08	3.92	125.00	2.50	309.2
43.00	6.78	3.92	13.04	3.92	152.00	2.50	194.8
53.00	14.98	3.92	13.08	3.92	111.00	2.50	234.5
65.00	12.82	3.92	14.58	3.92	43.00	2.50	87.2
72.00	10.97	5.67	15.32	5.67	215.00	4.00	500.2
87.00	13.46	5.08	11.14	5.08	205.00	3.50	398.2
98.00	18.54	5.08	13.06	5.08	240.00	3.50	698.3
109.00	6.50	4.50	18.77	4.50	91.00	3.00	202.2
119.00	10.54	4.50	18.72	4.50	92.00	3.00	233.0
1211.00	15.54	4.50	10.15	4.50	133.00	3.00	264.8
1312.00	14.88	4.50	15.13	4.50	87.00	3.00	215.8
1413.00	15.44	4.50	14.48	4.50	78.00	3.00	192.7

1514.00	19.97	3.63	15.92	3.63	86.00	2.25	279.6
1614.00	19.88	3.92	15.62	3.92	66.00	2.50	213.9
1714.00	11.16	4.50	15.05	4.50	220.00	3.00	444.6

TOTAL EARTH VOLUME FOR SEWER TRENCHES = 4555.006 CUBIC YARDS  
 SEWER FLOW LINE IS DETERMINED BY THE USER

EARTH VOLUME WAS ESTIMATED TO HAVE

BOTTOM WIDTH=DIAMETER OR WIDTH OF SEWER + 2 \* B

B=ONE FEET WHEN DIAMETER OR WIDTH <=48 INCHES

B=TWO FEET WHEN DIAMETER OR WIDTH >48 INCHES

IF BOTTOM WIDTH <MINIMUM WIDTH, 2 FT, THE MINIMUM WIDTH WAS USED.

BACKFILL DEPTH UNDER SEWER WAS ASSUMED TO BE ONE FOOT

SEWER WALL THICKNESS=EQIVLNT DIAMATER IN INCH/12 +1 IN INCHES



CIRCULAR CHANNEL ANALYSIS  
NORMAL DEPTH COMPUTATION

December 21, 1994

PROGRAM INPUT DATA:

DESCRIPTION	VALUE
Flow Rate (cubic feet per second).....	49.2
Channel Bottom Slope (feet per foot).....	0.0050
Manning's Roughness Coefficient (n-value).....	0.0130
Channel Diameter (feet).....	3.00

PROGRAM RESULTS:

DESCRIPTION	VALUE
Normal Depth (feet).....	2.60
Flow Velocity (feet per second).....	7.57
Froude Number (Flow is Sub-Critical).....	0.747
Velocity Head (feet).....	0.89
Energy Head (feet).....	3.49
Cross-Sectional Area of Flow (square feet).....	6.51
Top Width of Flow (feet).....	2.04

CIRCULAR CHANNEL ANALYSIS COMPUTER PROGRAM, Version 1.5 (c) 1986  
Dodson & Associates, Inc., 7015 W. Tidwell, #107, Houston, TX 77092  
(713) 895-8322. A complete program manual is available.

BASIN J. NOT DETAINED. FLOWING OFFSPILL (A = 0.28 AC)

$$A_T = 16.81 - 0.28$$

$$A_T = 16.53 \text{ AC}$$

100 YEAR -

$$V_{100} = K_{100} A_T$$

$$K_{100} = (1.78 I - 0.002 I^2 - 3.56) / 100$$

$$I = 80\% \text{ IMPERVIOUS}$$

$$K_{100} = 0.126$$

$$A_T = 16.53 \text{ AC}$$

$$V_{100} = (0.126)(16.53)$$

$$\underline{\underline{V_{100} = 2.08 \text{ AC} \cdot \text{FT} (90605 \text{ CF})}}$$

10 YEAR -

$$V_{10} = K_{10} A_T$$

$$K_{10} = (0.95 I - 1.90) / 1000$$

$$I = 80\%$$

$$K_{10} = 0.074$$

$$A_T = 16.53$$

$$V_{10} = (0.074)(16.53)$$

$$\underline{\underline{V_{10} = 1.22 \text{ AC} \cdot \text{FT} (53143 \text{ CF})}}$$

V<sub>100</sub> = 90605 CF


V<sub>10</sub> = 53143 CF

<u>ELEV</u> <u>(FT)</u>	<u>AREA</u> <u>(SF)</u>	<u>VOLUME</u> <u>(CF)</u>	<u>Z VOLUME</u> <u>(CF)</u>
6	0	3610	3610
7	7220	10040	13650
8	12860	16463	30113
9	20,066	21518	51631
10	22,970	24440	76071
11	25884		

10	51,631	11	76071
10.1	54075	11.6	92136
10.09	53831	11.1	78749
10.07	53343	11.2	81427
* 10.06		11.4	86783
		11.5	89461
		* 11.54	

10 YR POND ELEV

100 YR POND ELEV



BASIN J. NOT DETAINED

$$Q_{10} = 1.43 \text{ CFS}$$

$$Q_{100} = 2.34 \text{ CFS}$$

$$A_T = 16.81$$

⇒ FROM DOUGLAS COUNTY STORM DRAINAGE DESIGN AND TECHNICAL CRITERIA

$$Q_{100R} = 1.0 \text{ CFS/AC}$$

$$Q_{10R} = 0.30 \text{ CFS/AC}$$

$$100\text{YR} - Q_R = (1.0)(16.81) - 2.34$$


$$Q_{100R} = 14.47 \text{ CFS} *$$

$$10\text{YR} - Q_R = (0.30)(16.81) - 1.43$$

$$= 3.61 \text{ CFS} *$$

\* NOTE

BASIN J DEVELOPED RUNOFF  
SUBTRACTED FROM RELEASE  
RATE FOR TOTAL AREA.



MINOR STORM :

$Q_{OR} = 3.61 \text{ CFS}$

FLOW THROUGH 18 RCP

$A = 1.76 \text{ SF}$

$C = 0.65$

$H = 3.38$

$Q = CA\sqrt{2gh}$

$= (0.65)(1.76)\sqrt{64.4(3.38)}$

$= 14.70 \text{ CFS} > 3.61 \text{ CFS}$

⇒ USE ORIFICE PLATE



h (FT)	$\alpha$ (RAD)	AREA (FT <sup>2</sup> )	H (FT)	Q (CFS)
1.50	3.14	1.37	3.31	16.77
1.25	2.30	1.57	3.31	14.93
0.9	1.23	0.52	3.38	4.95
0.4	1.08	0.38	3.77	3.83
0.3	0.92	0.25	3.77	2.55
0.39	1.07	0.37	3.77	3.70

$\alpha = \cos^{-1} \left[ \frac{0.75 - h}{0.75} \right]$

$A = r^2 (\alpha - \sin \alpha \cos \alpha)$

$H = 3.31 + 2/3r \left[ \frac{\sin^3 \alpha}{\alpha - \sin \alpha \cos \alpha} \right]$

h = 0.39

MAJOR STORM

$Q_{100R} = 14.47 \text{ CFS}$

FLOW IN 18" (MINOR STORM)

$A = 0.37$

$H = 3.77 + 1.48 = 5.25'$

$Q = CA\sqrt{2gh}$

$Q = 4.42 \text{ CFS}$

GRATE NEEDS TO BE SIZED FOR A FLOW  $Q = 14.47 - 4.42$

$Q = 10.05 \text{ (SEE SHT 4 OF 6)}$

FLOW THROUGH 18" (MAJOR STORM)

$A = 1.77 \text{ SF}$

$C = 0.65$


$H = 5.06$

$Q = CA\sqrt{2gh}$

$= (0.65)(1.77)\sqrt{64.4(5.06)}$

$Q = 20.77 \text{ CFS} > 14.47 \text{ CFS}$

⇒ USE ORIFICE PLATE



$\alpha = \cos^{-1} \left[ \frac{0.75 - h}{0.75} \right]$

$A = r^2 (\alpha - \sin \alpha \cos \alpha)$

h (FT)	$\alpha$ (RAD)	AREA (FT <sup>2</sup> )	H (FT)	Q (CFS)
1.50	3.14	1.77	5.06	20.77
1.00	1.91	1.25	5.24	14.78
0.99	1.89	1.23	5.25	14.70
0.96	1.85	1.18	5.27	14.13
0.97	1.86	1.20	5.26	14.35 *

$H = 5.06 + \frac{2}{3} r \left[ \frac{\sin \alpha^3}{\alpha - \sin \alpha \cos \alpha} \right]$

USE  $h = 0.97'$

## SIZE INLET GRATE

$$Q = 10.05 \text{ CFS}$$

$$H = 1.40$$

$$C = 0.65$$

$$A = \frac{Q}{C\sqrt{2gh}}$$

AREA NEEDED

$$A = 1.50 \text{ SF}$$

TRY 2x2.5 W/ 1" BARS ON 3" CENTERS

$$\text{AREA} = 4 \text{ SF}$$

$$\# \text{ OF BARS } \frac{30}{3} = 10$$


$$\text{AREA OF BARS } 1/2 \times 2 \times 10 = 1.67 \text{ SF}$$

$$\begin{aligned} \text{AREA OPEN} &= 4.0 - 1.67 \\ &= 2.33 \end{aligned}$$


FLOW THROUGH INLET

$$Q = 14.70 \text{ CFS} > 10.05 \text{ OK}$$

⇒ ORIFICE PLATE WILL CONTROL  
OUTLET FLOW.



MINOR STORM  
CONTROL  
ORIFICE  
PLATE



MAJOR STORM  
CONTROL  
ORIFICE  
PLATE



OVERFLOW WEIR CALC. (DETENTION POND)

$$Q_0 = 14.47 \text{ CFS}$$

1.0' FREE BOARD


$$Q = CLH^{3/2}$$

$$C = 3.0$$

$$L = \frac{Q}{CH^{3/2}} = \frac{14.47}{(3.00)(1.0)^{3/2}}$$

$$L = 4.82'$$

LENGTH MUST NOT BE LESS THAN 4.82'



SIZING INTO POND FROM STORM LINE A

$$Q_D = 55.86 \text{ CFS}$$

$$S_o = 0.63\%$$

$$n = .013$$

$$D = 36''$$

DETERMINE CRITICAL DEPTH:

$$Z = \frac{Q}{\sqrt{g}} = \frac{55.86}{\sqrt{32.2}} = 9.84$$

$$\frac{Z}{D^{2.5}} = \frac{9.84}{3^{2.5}} = 0.63$$

$$\text{FIG 2-3 } Y_c/d = 0.80 \quad Y_c = 0.80(3) = 2.4'$$

DETERMINE NORMAL DEPTH:

$$AR^{2/3} = \frac{nQ}{1.49\sqrt{S}} = \frac{(.013)(55.86)}{1.49\sqrt{.0063}} = 6.14 \quad \frac{AR^{2/3}}{D^{8/3}} = \frac{6.14}{18.72} = 0.32$$

$$\text{FIG 2-2 } Y_n/d = 0.84 \quad Y_n = 0.84(3) = 2.52'$$

 $Y_n > Y_c$  SUBCRITICAL

$$D_a = 1/2(D + Y_n) = 2.76 \quad \frac{Q}{D_a^{1.5}} = 12.18 \quad \text{ASSUME } Y_T/d = 0.40$$

 $\Rightarrow$  FIG 5-7 USE TYPE M  $\phi = 12''$ 

DETERMINE LENGTH:

$$L = \left( \frac{1}{2 \tan \phi} \right) \left( \frac{Y_T}{Y_n} - W \right) \quad \frac{Q}{D_a^{2.5}} = \frac{55.86}{2.76^{2.5}} = 4.41 \quad \frac{Y_T}{H} = .40 \quad \text{FIG 5-9} = \frac{1}{2 \tan \phi} = 3.0$$

$$A = 7.06 \quad Y_T = .40(3) = 1.20$$

$$L = 3.0 \left( \frac{7.07}{1.20} - 3 \right) = 8.66$$

USE 9 LF TYPE M RIPRAP  $\phi = 12''$

-sizing INTO POND FROM STORM LINE B

$Q_0 = 49.23$  CFS

$S_0 = 0.50\%$

$n = .013$

$D = 36"$

DETERMINE CRITICAL DEPTH:

$Z = \frac{Q}{\sqrt{g}} = \frac{49.23}{\sqrt{32.2}} = 8.67$        $\frac{Z}{d^{2.5}} = \frac{8.67}{3^{2.5}} = 0.55$

FIG 2-3  $Y_c/d = 0.75$        $Y_c = 0.75(3) = 2.25'$

DETERMINE NORMAL DEPTH:

$AR^{2/3} = \frac{nQ}{1.49\sqrt{S_0}} = \frac{(.013)(49.23)}{1.49\sqrt{0.005}} = 6.07$        $\frac{AR^{2/3}}{D^{8/3}} = \frac{6.07}{18.72} = 0.32$

FIG 2-2  $Y_n/d = 0.84$        $Y_n = 0.84(3.0) = 2.52$

$Y_n > Y_c \Rightarrow$  SUBCRITICAL

$D_a = 1/2(D + Y_n) = 2.76$        $\frac{Q}{D_a^{1.5}} = 10.73$  ASSUME  $Y_T/d = .40$

$\Rightarrow$  FIG 5-7 USE TYPE M RIPRAP  $\phi = 12"$

DETERMINE LENGTH:

$L = \left(\frac{H}{2T}\right) \left(\frac{AT - W}{Y_T}\right)$        $\frac{Q}{D_a^{2.5}} = \frac{49.23}{12.65} = 3.89$        $\frac{Y_T}{H} = 0.40$

FIG 5-9  $\frac{L}{2TAN\phi} = 3.90$

$A = 7.06$        $Y_T = 0.40(3) = 1.20$

$L = 3.90 \left(\frac{7.06}{1.20} - 3\right) = 11.25$

USE 12 LF TYPE M RIPRAP  $\phi = 12"$

## SIZING OUT OF POND

$$Q_D = 14.47 \text{ CFS}$$

$$S_0 = 0.5\%$$

$$n = .013$$

$$D = 18''$$

## DETERMINE CRITICAL DEPTH:

$$Z = \frac{Q}{\sqrt{g}} = \frac{14.47}{\sqrt{32.2}} = 2.55 \quad \frac{Z}{D^{2.5}} = \frac{2.55}{1.5^{2.5}} = 0.92$$

$$\text{FIG 2-3 } Y_c/d = 0.94 \quad Y_c = 0.94(1.5) = 1.41$$

## DETERMINE NORMAL DEPTH:

$$AR^{2/3} = \frac{nQ}{1.49\sqrt{S}} = \frac{(.013)(14.47)}{1.49\sqrt{0.005}} = 1.78 \quad \frac{AR^{2/3}}{D^{8/3}} = \frac{1.78}{1.5^{8/3}} = 0.60$$

$$\text{FIG 2-2 } Y_n/d = 1.0 \quad Y_n = 1.0(1.5) = 1.50$$

$$Y_n > Y_c$$

$$D_a = 1/2(D + Y_n) = 1.50 \quad Q/D_a^{1.5} = 7.88 \quad \text{ASSUME } Y_T/d = 0.40$$

⇒ FIG 5-7 USE TYPE L  $\phi = 9''$

## DETERMINE LENGTH:

$$L = \left( \frac{Q}{2 \tan \phi} \right) \left( \frac{AT - W}{Y_T} \right) \quad \frac{Q}{D_a^{2.5}} = 5.25 \quad Y_T/H = 0.40 \quad \text{FIG 5-9 } \frac{L}{2 \tan \phi} = 2.20$$

$$A = 1.77 \quad Y_T = 0.40(1.5) = 0.60$$

$$L = (2.20) \left( \frac{1.77}{.60} - 1.5 \right) = 3.19$$


USE 5 LF TYPE L RIPRAP  $\phi = 9''$

SWALE BELOW DETENTION POND  
SECTION AA ON DRAINAGE PLAN

$$Q_D = 14.47$$

$$S_o = 4.31\%$$

$$n = .035$$



$$A = 8.05F$$

$$WP = 6.32$$

$$Q = 16.14 \text{ CFS} > 14.47 \text{ CFS} \quad \text{OK}$$

\* NOTE


SWALE WILL BE TEMPORARY

AND WILL FLOW DOWN TO

DETENTION POND FROM MASTER

DRAINAGE STUDY

Q req'd = 14.47 CFS  
 Length of Swale = 908 LF  
 Change in Elevation = 38'  
 S<sub>avg</sub> = 4.19%



Channel Cross Section

S<sub>avg</sub> = 4.19%  
 n = 0.035  
 V = 1.49/n R<sub>h</sub><sup>2/3</sup> S<sup>1/2</sup>  
 A = 2.80  
 W<sub>p</sub> = 6.11  
 R<sub>h</sub> = 0.458  
 V = 5.18 FPS  
 D = 0.97'

S<sub>max</sub> = 6.32%  
 n = 0.035  
 A = 2.40  
 W<sub>p</sub> = 5.66  
 R<sub>h</sub> = 0.424  
 V = 6.04 FPS  
 D = 0.89 FEET

S<sub>min</sub> = 1.00%  
 n = 0.035  
 A = 4.79  
 W<sub>p</sub> = 7.97  
 R<sub>h</sub> = 0.60  
 V = 3.02 FPS  
 D = 1.26 FEET


Maximum Velocity = 6.0 FPS  
 Minimum Freeboard = 0.74'

TABLE 3-1 (42)  
RECOMMENDED RUNOFF COEFFICIENTS AND PERCENT IMPERVIOUS

LAND USE OR SURFACE CHARACTERISTICS	PERCENT IMPERVIOUS	FREQUENCY			
		2	5	10	100
<u>Business:</u>					
Commercial Areas	95	.87	.87	.88	.89
Neighborhood Areas	70	.60	.65	.70	.80
<u>Residential:</u>					
Single-Family	*	.40	.45	.50	.60
Multi-Unit (detached)	50	.45	.50	.60	.70
Multi-Unit (attached)	70	.60	.65	.70	.80
1/2 Acre Lot or Larger	*	.30	.35	.40	.60
Apartments	70	.65	.70	.70	.80
<u>Industrial:</u>					
Light Areas	80	.71	.72	.76	.82
Heavy Acres	90	.80	.80	.85	.90
<u>Parks, Cemeteries:</u>	7	.10	.18	.25	.45
<u>Playgrounds:</u>	13	.15	.20	.30	.50
<u>Schools:</u>	50	.45	.50	.60	.70
<u>Railroad Yard Areas</u>	20	.20	.25	.35	.45
<u>Undeveloped Areas:</u>					
Historic Flow Analysis-	2	(See "Lawns")			
Greenbelts, Agricultural					
Offsite Flow Analysis (when land use not defined)	45	.43	.47	.55	.65
<u>Streets:</u>					
Paved	100	.87	.88	.90	.93
Gravel (Packed)	40	.40	.45	.50	.60
<u>Drive and Walks:</u>	96	.87	.87	.88	.89
<u>Roofs:</u>	90	.80	.85	.90	.90
<u>Lawns, Sandy Soil</u>	0	.00	.01	.05	.20
<u>Lawns, Clayey Soil</u>	0	.05	.15	.25	.50

NOTE: These Rational Formula coefficients may not be valid for large basins.

\*See Figure 2-1 for percent impervious.




**TABLE A**  
 PROPOSED BASIN SUMMARY

BASIN DESIGNATION	AREA (AC)	C <sub>1</sub>	C <sub>2</sub>	T <sub>1</sub> (MIN)	C <sub>1</sub> P <sub>1</sub>	C <sub>2</sub> P <sub>2</sub>
A	6.01	.21	.27	7.27	21.25	21.25
B	1.99	.28	.28	5.89	8.89	13.76
C	1.08	.21	.28	7.28	8.48	1.75
D	1.49	.27	.27	5.89	6.58	16.88
E	1.76	.28	.28	5.89	7.28	14.2
F	1.76	.28	.28	5.89	7.28	14.2
G	0.45	.31	.42	7.28	1.28	2.34
H	0.64	.46	.28	7.28	2.16	2.8
I	0.88	.41	.71	2.89	2.65	1.8
J	0.28	.28	.28	5.89	1.28	2.34

**TABLE B**  
 DESIGN POINT SUMMARY

DESIGN POINT	CONTRIBUTING BASIN	AREA (AC)	C <sub>1</sub> (CFS)	C <sub>2</sub> (CFS)
1A	A	6.01	2.39	2.39
1	A	6.01	19.42	37.69
2A	B	1.99	2.39	2.39
2	B	1.99	5.89	13.76
3	D	1.49	4.90	16.88
4	E	1.76	7.28	14.2
5	F	1.76	7.28	14.2
6	G	0.45	1.28	2.34
7	H	0.64	2.16	2.8
8	I	0.88	2.65	1.8



**LEGEND**

- PROP. CONTOUR ——— 5510 ———
- EXIST. CONTOUR ——— 5500 ———
- BASIN BOUNDARY - - - - -
- SUB-BASIN BOUNDARY - - - - -
- DIRECTION OF FLOW →
- DESIGN POINT 1
- BASIN B C5 CFS
- AREA IN ACRES C100 CFS

date AUGUST 24, 1994  
 job number 12426.01  
 design by A. KELLY  
 drawn by A. KELLY  
 checked by G. THOMAS

COUNTY ENGINEER \_\_\_\_\_  
 DATE \_\_\_\_\_

THESE CONSTRUCTION PLANS HAVE BEEN REVIEWED BY DOUGLAS COUNTY FOR STREET AND DRAINAGE IMPROVEMENTS ONLY.

ENGINEERING DIVISION ACCEPTANCE BLOCK

**MARTIN/MARTIN**  
 Consulting Engineers  
 4251 Kipling St.  
 Wheat Ridge, Co.  
 (303) 431-6100

**PROJECT MAJESTIC**  
**DRAINAGE PLAN**

no	description of revisions	date	name
1	DETENTION POND RELOCATION	12-13-94	DAL
2	REVISED PER COUNTY COMMENTS	02-22-95	JCM

sheet number  
 12426.01  
**D1**

MARTIN/MARTIN assumes no responsibility for utility locations. The utilities shown on this drawing have been plotted from the best available information. It is, however, the contractor's responsibility to field verify the location of all utilities prior to the commencement of any construction.